

Table of Contents

Hardware Limited Warranty	xiii
Preface	xiv
1. Introduction and Specifications	1-1
1.1 System Configuration Concepts	1-4
1.1.1 IFD IF Digitizer	1-9
1.1.2 Digital Receiver PCI Card (RVP8/Rx)	1-10
1.1.3 Mother Board or Single-Board Computer (SBC)	1-13
1.1.4 Digital Transmitter PCI Card (RVP8/Tx)	1-13
1.1.5 I/O-62 PCI Card and I/O Panel	1-15
1.2 Comparison of Analog vs Digital Radar Receivers	1-17
1.2.1 What is a Digital IF Receiver?	1-17
1.2.2 Magnetron Receiver Example	1-18
1.2.3 Klystron or TWT Receiver and Transmit RF Example	1-20
1.3 RVP8 IF Signal Processing	1-21
1.3.1 IFD Data Capture and Timing	1-21
1.3.2 Burst Pulse Analysis for Amplitude/Frequency/Phase	1-22
1.3.3 Rx Board and CPU IF to I/Q Processing	1-23
1.4 RVP8 Weather Signal Processing	1-25
1.4.1 General Processing features	1-26
1.4.2 RVP8 Pulse Pair Time Domain Processing	1-29
1.4.3 RVP8 DFT/FFT Processing	1-29
1.4.4 Random Phase Processing for 2nd Trip Echo	1-30
1.4.5 Polarization Mode Processing	1-30
1.4.6 Output Data	1-30
1.5 RVP8 Control and Maintenance Features	1-31
1.5.1 Radar Control Functions	1-31
1.5.2 Power-Up Setup Configuration	1-32
1.5.3 Built-In Diagnostics	1-32
1.6 Support Utilities and Available Application Software	1-33
1.7 System Network Architecture	1-34
1.8 Open Architecture and Published API	1-35
1.9 RVP8 Technical Specifications	1-36
1.9.1 IFD Digitizer Module	1-36
1.9.2 RVP8/Rx PCI Card	1-37
1.9.3 RVP8/Tx PCI Card	1-38
1.9.4 SIGMET I/O-62 PCI Card	1-39
1.9.5 RVP8 Standard Connector Panel	1-40

1.9.6	RVP8 Processing Algorithms	1-41
1.9.7	RVP8 Input/Output Summary	1-43
1.9.8	Physical and Environmental Characteristics	1-44
2.	Hardware Installation	2-1
2.1	Overview and Input Power Requirements	2-1
2.2	IFD IF Digitizer Module Installation	2-2
2.2.1	IFD Introduction	2-2
2.2.2	IFD Revision History	2-3
2.2.3	IFD Power, Size and Physical Mounting Considerations	2-4
2.2.4	IFD I/O Summary	2-5
2.2.5	IFD Adjustments and Test/Status Indicators	2-6
2.2.6	IFD Input A/D Saturation Levels	2-8
2.2.7	IF Bandwidth and Dynamic Range	2-9
2.2.8	IF Gain and System Performance	2-11
2.2.9	IF Gain Based on System Noise Figure	2-13
2.2.10	Choice of Intermediate Frequency	2-14
2.2.11	IFD Analog AFC Output Voltage (Optional)	2-15
2.2.12	IFD Reference Clock Input (Optional)	2-15
2.2.13	Communications Between the IFD and RVP8/Rx	2-17
2.2.14	Summary of Crystal and Filter Configurations	2-18
2.3	RVP8 Chassis	2-20
2.3.1	RVP8 Chassis Overview	2-20
2.3.2	Power Requirements, Size and Physical Mounting	2-20
2.3.3	Main Chassis Direct Connections	2-21
2.3.4	External Pre-Trigger Input	2-22
2.3.5	Connector Panel I/O Connections	2-22
2.3.6	Power-Up Details	2-26
2.3.7	Socket Interface	2-27
2.4	Digital AFC Module (DAFC)	2-30
2.4.1	Example Hookup to a CTI "MVSr-xxx" STALO	2-32
2.4.2	Example Hookup to a MITEQ "MFS-xxx" STALO	2-34
2.5	RVP8 Custom Interfaces	2-35
2.5.1	Using the IFD Coax Uplink	2-35
3.	TTY Nonvolatile Setups	3-1
3.1	Overview of Setup Procedures	3-1
3.1.1	Factory, Saved, and Current Settings	3-2
3.1.2	V — View Card and System Status	3-3
3.2	View/Modify Dialogs	3-6
3.2.1	Mc — Top Level Configuration	3-6
3.2.2	Mp — Processing Options	3-8
3.2.3	Mf — Clutter Filters	3-12

3.2.4	Mt — General Trigger Setups	3-14
3.2.5	Mt<n> — Triggers for Pulsewidth #n	3-17
3.2.5.1	Special Options for Tx Synthesis	3-21
3.2.6	Mb — Burst Pulse and AFC	3-25
3.2.6.1	AFC Motor/Integrator Option	3-32
3.2.7	M+ — Debug Options	3-33
3.2.8	Mz — Transmissions and Modulations	3-34
3.3	Advanced Options	3-36
3.3.1	“*” — Sample current noise levels	3-36
3.3.2	“@” — Display/Change current Major Mode	3-36
3.3.3	“~” — Burst-In / IF-In Swap Command (Rev.D IFD)	3-36
4.	Plot-Assisted Setups	4-1
4.1	P+ — Plot Test Pattern	4-2
4.2	General Conventions Within the Plot Commands	4-3
4.3	Pb — Plot Burst Pulse Timing	4-5
4.3.1	Interpreting the Burst Timing Plot	4-5
4.3.2	Available Subcommands Within “Pb”	4-6
4.3.3	TTY Information Lines Within “Pb”	4-7
4.3.4	Recommended Adjustment Procedures	4-8
4.4	Ps — Plot Burst Spectra and AFC	4-10
4.4.1	Interpreting the Burst Spectra Plots	4-10
4.4.2	Available Subcommands Within “Ps”	4-12
4.4.3	TTY Information Lines Within “Ps”	4-14
4.4.4	Computation of Filter Loss	4-16
4.4.5	Recommended Adjustment Procedures	4-19
4.5	Pr — Plot Receiver Waveforms	4-22
4.5.1	Interpreting the Receiver Waveform Plots	4-22
4.5.2	Available Subcommands Within “Pr”	4-24
4.5.3	TTY Information Lines Within “Pr”	4-25
4.6	Pa — Plot Tx Waveform Ambiguity	4-27
4.6.1	Interpreting the Ambiguity Plots	4-27
4.6.2	Available Subcommands Within “Pa”	4-29
4.6.3	TTY Information Lines Within “Pa”	4-30
4.6.4	Bench Testing of Compressed Waveforms	4-32
5.	Processing Algorithms	5-1
5.1	IF Signal Processing	5-4
5.1.1	FIR (Matched) Filter	5-4
5.1.2	Automatic Frequency Control (AFC)	5-5
5.1.3	Burst Pulse Tracking	5-6
5.1.4	Interference Filter	5-7
5.1.5	Large-Signal Linearization	5-9

5.1.6	Correction for Tx Power Fluctuations	5-9
5.2	Time Series ("I" and "Q") Signal Processing	5-11
5.2.1	Time Series Processing Overview	5-11
5.2.2	Frequency Domain Processing- Doppler Power Spectrum	5-13
5.2.3	Autocorrelations	5-16
5.2.4	Clutter Filtering Approaches	5-17
5.2.4.1	Fixed Width Clutter Filters	5-18
5.2.4.2	Variable Width Clutter Filter	5-19
5.2.4.3	Gaussian Model Adaptive Processing (GMAP)	5-20
5.2.5	Range averaging and Clutter Microsuppression	5-27
5.2.6	Reflectivity	5-27
5.2.7	Velocity	5-29
5.2.8	Spectrum Width Algorithms	5-29
5.2.9	Signal Quality Index (SQI threshold)	5-30
5.2.10	Clutter Correction (CCOR threshold)	5-31
5.2.11	Weather Signal Power (SIG threshold)	5-32
5.2.12	Signal to Noise Ratio (LOG threshold)	5-32
5.3	Thresholding	5-33
5.3.1	Threshold Qualifiers	5-33
5.3.2	Adjusting Threshold Qualifiers	5-34
5.3.3	Speckle Filters	5-35
5.4	Reflectivity Calibration	5-39
5.4.1	Plot Method for Calibration of I_o	5-39
5.4.2	Single-Point Direct Method for Calibration of I_o	5-40
5.4.3	Treatment of Losses in the Calibration	5-41
5.4.4	Determination of dBZ_o	5-42
5.5	Dual PRT Processing Mode	5-44
5.5.1	DPRT-1 Mode	5-44
5.5.2	DPRT-2 Mode	5-45
5.6	Dual PRF Velocity Unfolding	5-46
5.7	Random Phase 2nd Trip Processing	5-50
5.7.1	Overview	5-50
5.7.2	Algorithm	5-50
5.7.3	Tuning for Optimal Performance	5-51
5.8	Signal Generator Testing of the Algorithms	5-55
5.8.1	Linear Ramp of Velocity with Range	5-55
5.8.2	Verifying PHIDP and KDP	5-56
5.8.3	Verifying RHOH, RHOV, and RHOHV	5-56
5.8.4	Angle Synchronization	5-57
6.	Host Computer Commands	6-1
6.1	No-Operation (NOP)	6-2

6.2	Load Range Mask (LRMSK)	6-2
6.3	Setup Operating Parameters (SOPRM)	6-4
6.4	Interface Input/Output Test (IOTEST)	6-11
6.5	Interface Output Test (OTEST)	6-11
6.6	Sample Noise Level (SNOISE)	6-12
6.7	Initiate Processing (PROC)	6-14
6.8	Load Clutter Filter Flags (LFILT)	6-23
6.9	Get Processor Parameters (GPARM)	6-25
6.10	Load Simulated Time Series Data (LSIMUL)	6-35
6.11	Reset (RESET)	6-37
6.12	Define Trigger Generator Waveforms (TRIGWF)	6-37
6.13	Define Pulse Width Control and PRT Limits (PWINFO)	6-38
6.14	Set Pulse Width and PRF (SETPWF)	6-40
6.15	Load Antenna Synchronization Table (LSYNC)	6-40
6.16	Set/Clear User LED (SLED)	6-42
6.17	TTY Operation (TTYOP)	6-43
6.18	Load Custom Range Normalization (LDRNV)	6-44
6.19	Read Back Internal Tables and Parameters (RBACK)	6-45
6.20	Pass Auxiliary Arguments to Opcodes (XARGS)	6-46
6.21	Load Clutter Filter Specifications (LFSPECS)	6-47
6.22	Configure Ray Header Words (CFGHDR)	6-48
6.23	Configure Interference Filter (CFGINTF)	6-49
6.24	Set AFC level (SETAFC)	6-50
6.25	Set Trigger Timing Slew (SETSLEW)	6-50
6.26	Hunt for Burst Pulse (BPHUNT)	6-50
6.27	Configure Phase Modulation (CFGPHZ)	6-51
6.28	Set User IQ Bits (UIQBITS)	6-52
6.29	Set Individual Thresholds (THRESH)	6-52
6.30	Set Task Identification Information (TASKID)	6-53
6.31	Define PRF "Pie Slices" (PRFSECT)	6-54
6.32	Configure Target Simulator (TARGSIM)	6-55
6.33	Set Burst Pulse Processing Options (BPOPTS)	6-57
6.34	Custom User Opcode (USRINTR and USRCONT)	6-57
A.	Serial Control Formats	A-1
B.	Optional Dual Polarization- ZDR, PHIDP, KDP, LDR,	B-1
B.1	Overview of Dual Polarization	B-1
B.2	Radar System Considerations	B-3
B.3	RVP8 Dual-Channel Receiver Approach	B-5
B.4	Overview of Processing Algorithms	B-6
B.5	Case 1: Fixed Transmit: Dual-Channel Receiver	B-9
B.6	Case 2: Simultaneous Dual Transmit and Receive (STAR mode)	B-10

B.7 Case 3: Alternating H/V Transmit: Single-Channel Receiver	B-12
B.8 Case 4: Alternating H/V Transmit: Dual-Channel Receiver	B-13
B.9 KDP Calculation	B-14
B.10 Standard Moment Calculations (T, Z, V, W)	B-15
B.11 Thresholding of Polarization Parameters	B-25
B.12 Calibration Considerations	B-26
C. References and Credits	C-1
D. Installation and Test Procedure	D-1
D.1 Installation Check	D-3
D.2 Power-Up Check	D-4
D.3 Setup Terminal	D-5
D.4 Setup "V" Command (Internal Status)	D-6
D.5 Setup "Mc" Command (Board Configuration)	D-7
D.6 Setup "Mp" Command (Processing Options)	D-8
D.7 Setup "Mf" Command (Clutter Filters)	D-9
D.8 Setup "Mt" Command (General Trigger Setup)	D-10
D.9 Initial Setup of Information for Each Pulse Width	D-11
D.10 Setup "Mb" Command (Burst Pulse and AFC)	D-12
D.11 Setup "M+" Command (Debug Options)	D-13
D.12 Setup "Mz" Command (Transmitter Phase Control)	D-14
D.13 A-Scope Test	D-15
D.14 Burst Pulse Alignment	D-16
D.15 Bandwidth Filter Adjustment	D-17
D.16 Digital AFC (DAFC) Alignment (Optional)XXX	D-18
D.17 Analog AFC Voltage Alignment (Optional)	D-19
D.18 MFC Functional Test and Tuning (Optional)	D-21
D.19 AFC Functional Test (Optional)	D-22
D.20 Input IF Signal Level Check	D-23
D.21 Dynamic Range Check	D-24
D.22 Receiver Bandwidth Check	D-26
D.23 Receiver Phase Noise Check	D-28
D.24 Hardcopy and Backup of Final Setups	D-29
D.25 IFD Stand-alone SigGen Bench Test	D-30
D.26 RVP8/Tx Stand-alone Bench Test	D-31
D.27 RVP8/Rx Stand-alone Bench Test	D-32
E. RVP8 Developer's Notes (draft)	E-1
E.1 Organization of the RDA Software	E-1
E.2 RVP8 Overall Code Organization	E-1
E.2.1 RVP8 Software Maintenance Model	E-2
E.2.2 Installing Incremental RDA Upgrades	E-3

E.2.3 Rebuilding the RDA Linux Kernel Module	E-3
E.3 Debugging and Profiling Your Code	E-4
E.3.1 Monitoring Opcode/Data Activity: <code>-exposeIO</code>	E-4
E.3.2 Showing Live Acquired Pulse Info: <code>-showAQ</code>	E-5
E.3.3 Showing Coherent Processing Intervals: <code>-showCPIs</code>	E-6
E.3.4 Showing RealTime Callback Timers: <code>-showRTCtrl</code>	E-6
E.3.5 Using <code>ddd</code> on the Main & Proc Code	E-7
E.3.6 Finding memory leaks with <code>valgrind</code>	E-8
E.3.7 Profiling with <code>gprof</code>	E-8
E.4 Creating New Major Modes from Old Ones	E-9
E.4.1 Function Pointers are the Key to Customization	E-9
E.4.2 <code>init/exitMajorMode()</code> and <code>init/exitProcSection()</code>	E-9
E.4.3 Responsibilities of RVP8/Main Threads	E-9
E.4.4 Responsibilities of RVP8/Proc Processes	E-9
E.5 Real-Time Control of the RVP8	E-9
E.5.1 Using the Programmable Callback Timers	E-9
E.5.2 Synchronizing Trigger and Antenna Events	E-9
E.5.3 Example RealTime Interrupt Histogram	E-9
E.6 Customizing the (I,Q) Data Stream	E-9
E.6.1 Defining the FIR Matched Filter	E-9
E.6.2 Applying Raw Pulse Corrections	E-9
E.6.3 Inserting <code>UserIQ</code> Header BIts	E-9
E.7 Customizing the Front Panel Display	E-9
E.8 Adding Custom DSP/Lib Opcodes	E-9
E.9 Using the Softplane for Physical I/O	E-10
E.9.1 Softplane Programmer's Model	E-10
E.9.2 Reducing Unnecessary PCI Traffic	E-10
E.10 Handling Live Antenna Angles	E-10
E.11 Creating Custom Trigger Sequences	E-10
E.11.1 Defining Trigger Waveshapes	E-10
E.11.2 Defining Trigger PRT Sequences	E-10
E.11.3 Polarization and Phase Control	E-10
E.12 Determining CPI's and Ray Boundaries	E-10
E.13 Using the RVP8 TimeSeries API	E-10
E.13.1 Reader and Writer Clients	E-10
E.13.2 Attach/Detach Details	E-11
E.13.3 Extracting Pulses via Sequence Numbers	E-11
E.13.4 Using Memory Bandwidth Effectively	E-11
E.13.5 Packed and Floating Data Formats	E-11
E.14 Using the Intel IPP Library	E-11
F. Time Series Recording	F-1
F.1 Overview	F-1

F.2	TS Record/Playback Software Architecture	F-2
F.2.1	General Architecture	F-2
F.2.2	Description of Processes	F-2
F.3	Installation & Configuration	F-4
F.3.1	Required Software	F-4
F.3.2	Configuring UDP Ports	F-4
F.3.3	Configuring automatic start-up of tsimport & tsexport	F-4
F.3.4	Configuring Network buffering for tsimport	F-5
F.3.5	Tsimport and Tsexport from the command line	F-5
F.4	Tsswitch Utility	F-6
F.5	Tsarchive Utility	F-7
F.5.1	Archive Directory Area	F-7
F.5.2	TS Source	F-8
F.5.3	Filter	F-9
F.5.4	TS Archive Log Area	F-10
F.6	Specific Software Application Examples	F-12
F.6.1	Case 1: TS recording on a local RVP8	F-13
F.6.2	Case 2: TS recording on separate archive host	F-14
F.6.3	Case 3: TS playback on a local RVP8	F-15
F.6.4	Case 4: TS playback from a separate archive host to an RVP8	F-16
F.6.5	Quick Guides	F-17
F.7	Ascope Playback Features	F-18
F.8	TS Viewing Utility (tsview)	F-21
F.8.1	Overview	F-21
F.8.2	Starting tsview and Sample Session	F-21
F.8.3	Tsview Command Line Options	F-22
F.9	TS Record Data Format	F-25
G.	RVP8/RCP8 Packaging	G-1
G.1	Main Chassis General Description	G-2
G.1.1	Main Chassis Front Panel	G-7
G.1.2	Main Chassis Back Panel	G-8
G.1.3	Main Chassis Back Panel Power Section	G-9
G.1.4	Main Chassis Back Panel PC I/O Section	G-10
G.1.5	Main Chassis Back Panel PCI Card Section	G-11
G.2	I/O-62 and Connector Panel	G-14
G.3	IFD Module (RVP8 Only)	G-30
G.4	DAFC Module (RVP8 only)	G-33
Index Index	
-1		

Figures

Figure 1-1:	Analog vs Digital Receiver for Magnetron Systems	1-19
Figure 1-2:	Analog vs Digital Receiver for Klystron Systems	1-20
Figure 1-3:	IF to I/Q Processing Steps	1-23
Figure 1-4:	I/Q Processing for Weather Moment Extraction	1-26
Figure 1-5:	Network Architecture for Socket Interface with DspExport	1-34
Figure 2-1:	Calibration Plot for a Stand-alone 14-Bit IFD	2-10
Figure 2-2:	Tradeoff Between Dynamic Range and Sensitivity	2-11
Figure 2-3:	Assembly Diagram of the DAFC	2-30
Figure 2-4:	Recommended Receiving Circuit for the Coax Uplink	2-35
Figure 2-5:	Timing Diagram of the IFD Coax Uplink	2-36
Figure 4-1:	The Test Pattern Display	4-2
Figure 4-2:	Successful Capture of the Transmit Burst	4-5
Figure 4-3:	Example of a Filter With Excellent DC Rejection	4-10
Figure 4-4:	Example of a Poorly Matched Filter	4-19
Figure 4-5:	Example of a Filter With Poor DC Rejection	4-21
Figure 4-6:	Example of Combined IF Sample and LOG Plot	4-22
Figure 4-7:	Example of a Noisy High Resolution "Pr" Spectrum	4-24
Figure 4-8:	Ambiguity Diagram of a Compressed Tx Pulse	4-27
Figure 4-9:	Frequency, Phase and Amplitude of a Compressed Tx Pulse	4-28
Figure 4-10:	IFD Sampling of Optimized Compressed Tx Waveform	4-32
Figure 4-11:	Ideal and Actual Linear-FM Spectrum Displayed in Ps Plot	4-33
Figure 5-1:	Flow Diagram of RVP8 Processing	5-3
Figure 5-2:	Linearization of Saturated Signals Above +4.5dBm (Rev B/C IFD) .	5-10
Figure 5-3:	Example of time series and Doppler power spectrum	5-12
Figure 5-4:	Typical form of a time series window	5-14
Figure 5-5:	Impulse response of a typical window	5-15
Figure 5-6:	Example of fixed width	5-18
Figure 5-7:	Variable Width Clutter Filter	5-19
Figure 5-8:	GMAP Algorithm Steps	5-21
Figure 5-9:	GMAP example	5-26
Figure 5-10:	Model Intensity Curve	5-39
Figure 5-11:	Illustration of Losses that Affect LOG Calibration	5-42
Figure 5-12:	Dual PRF Concepts	5-47
Figure 5-13:	Example of Dual PRF Trigger Waveforms	5-49
Figure 5-14:	Random Phase Processing Algorithm	5-54
Figure B-1:	Least Squares KDP calculation	B-14
Figure G-1:	Main Chassis- Front Panel	G-3
Figure G-2:	Main Chassis- Back Panel	G-4
Figure G-3:	Main Chassis- Right Side View	G-5
Figure G-4:	Main Chassis Internal Cabling	G-6

Figure G-5: RVP8 I/O-62 Connector Panel	G-16
Figure G-6: RCP8 I/O-62 Connector Panel	G-17
Figure G-7: RVP8/IFD Module	G-31
Figure G-8: IFD Front Panel	G-32
Figure G-9: View of DAFC Module	G-33

Tables

Table 1-1: Examples of Dual PRF Velocity Unfolding	1-28
Table 2-1: Differences Among Versions of the IFD	2-3
Table 2-2: IFD Connectors (All Revisions)	2-5
Table 2-3: IFD Connectors (Rev.A-Rev.D)	2-5
Table 2-4: IFD Connectors (Rev.E & Greater)	2-5
Table 2-5: IFD Toggle Switch Settings	2-6
Table 2-6: IFD LED Indicator Interpretations	2-6
Table 2-7: IFD Internal Jumper Settings	2-7
Table 2-8: Clock Locking Component Options	2-19
Table 2-9: Direct Connections to RVP8 Main Chassis	2-21
Table 2-10: DAFC Protocol Jumper Selections	2-31
Table 2-11: Pinout for the CTI "MVSr-xxx" STALO	2-33
Table 2-12: Bit Assignments for the IFD Coax Uplink	2-36
Table 5-1: Algebraic Quantities Within the RVP8 Processor	5-2
Table 5-2: Algorithm Results for +16dB Interference	5-8
Table 5-3: Algorithm Results for +26dB Interference	5-9
Table 6-2: RVP8 Status Output Words	6-25
Table A-1: Internal BITE Packet (RCP8 to Host)	A-2
Table B-1: Transmitter Types	B-3
Table B-2: Supported Polarization Modes and Outputs	B-6
Table F-1: TS File Format	F-25
Table G-1: RVP8 and RCP8 I/O-62 Card Jumper Settings	G-12
Table G-2: RVP8/Rx Card Jumper Settings	G-13
Table G-3: RVP8/Tx Card Jumper Settings	G-13
Table G-4: J1 "AZ INPUT"	G-18
Table G-5: J2 "AZ OUTPUT"	G-19
Table G-6: J3 RVP8: "PHASE OUT"; RCP8 "CONTROL"	G-20
Table G-7: J4 "EL INPUT"	G-21
Table G-8: J5 "EL OUTPUT"	G-22
Table G-9: J6 "RELAY"	G-23
Table G-10: J7: RVP8 "SPARE"; RCP8 "BITE 19:0"	G-24
Table G-11: J8: RVP8 "SPARE"; RCP8 "ANALOG IN"	G-25
Table G-12: J9 RVP8: "MISC I/O" ; RCP8: "PED/STATUS"	G-26
Table G-13: J10 "SERIAL"	G-27
Table G-14: J11 "SERIAL"	G-27
Table G-15: J12 "S-D"	G-28
Table G-16: RVP8 BNC Connector Pin Assignments	G-29
Table G-17: RCP8 BNC Connector Pin Assignments	G-29