

Table of Contents

Hardware Limited Warranty	xii
Preface	xiii
1. Introduction and Specifications	1-1
1.1 System Configuration Concepts	1-4
1.1.1 IFD IF Digitizer	1-9
1.1.2 Digital Receiver PCI Card (RVP8/Rx)	1-10
1.1.3 Mother Board or Single-Board Computer (SBC)	1-13
1.1.4 Digital Transmitter PCI Card (RVP8/Tx)	1-13
1.1.5 I/O-62 PCI Card and I/O Panel	1-15
1.2 Comparison of Analog vs Digital Radar Receivers	1-17
1.2.1 What is a Digital IF Receiver?	1-17
1.2.2 Magnetron Receiver Example	1-18
1.2.3 Klystron or TWT Receiver and Transmit RF Example	1-20
1.3 RVP8 IF Signal Processing	1-21
1.3.1 IFD Data Capture and Timing	1-21
1.3.2 Burst Pulse Analysis for Amplitude/Frequency/Phase	1-22
1.3.3 Rx Board and CPU IF to I/Q Processing	1-23
1.4 RVP8 Weather Signal Processing	1-25
1.4.1 General Processing features	1-26
1.4.2 RVP8 Pulse Pair Time Domain Processing	1-29
1.4.3 RVP8 DFT/FFT Processing	1-29
1.4.4 Random Phase Processing for 2nd Trip Echo	1-30
1.4.5 Polarization Mode Processing	1-30
1.4.6 Output Data	1-30
1.5 RVP8 Control and Maintenance Features	1-31
1.5.1 Radar Control Functions	1-31
1.5.2 Power-Up Setup Configuration	1-32
1.5.3 Built-In Diagnostics	1-32
1.6 Support Utilities and Available Application Software	1-33
1.7 System Network Architecture	1-34
1.8 Open Architecture and Published API	1-35
1.9 RVP8 Technical Specifications	1-36
1.9.1 IFD Digitizer Module, Rev E or later	1-36
1.9.2 RVP8/Rx PCI Card	1-37
1.9.3 RVP8/Tx PCI Card	1-38
1.9.4 SIGMET I/O-62 PCI Card	1-39
1.9.5 RVP8 Standard Connector Panel	1-40

1.9.6	RVP8 Processing Algorithms	1-41
1.9.7	RVP8 Input/Output Summary	1-43
1.9.8	Physical and Environmental Characteristics	1-44
2.	Hardware Installation	2-1
2.1	Overview and Input Power Requirements	2-1
2.2	IFD IF Digitizer Module Installation	2-2
2.2.1	IFD Introduction	2-2
2.2.2	IFD Revision History	2-3
2.2.3	IFD Power, Size and Mounting Considerations	2-4
2.2.4	IFD I/O Summary	2-5
2.2.5	IFD Adjustments and Test/Status Indicators	2-6
2.2.6	IFD Input A/D Saturation Levels	2-8
2.2.7	IF Bandwidth and Dynamic Range	2-9
2.2.8	IF Gain and System Performance	2-11
2.2.9	IF Gain Based on System Noise Figure	2-13
2.2.10	Choice of Intermediate Frequency	2-14
2.2.11	IFD Analog AFC Output Voltage (Optional)	2-15
2.2.12	IFD Reference Clock Input (Optional)	2-15
2.2.13	Communications Between the IFD and RVP8/Rx	2-17
2.2.14	Summary of Crystal and Filter Configurations	2-18
2.3	RVP8 Chassis	2-20
2.3.1	RVP8 Chassis Overview	2-20
2.3.2	Power Requirements, Size and Physical Mounting	2-20
2.3.3	Main Chassis Direct Connections	2-21
2.3.4	External Pre-Trigger Input	2-22
2.3.5	Connector Panel I/O Connections	2-22
2.3.6	Power-Up Details	2-26
2.3.7	Socket Interface	2-27
2.4	Digital AFC Module (DAFC)	2-30
2.4.1	Example Hookup to a CTI "MVSr-xxx" STALO	2-32
2.4.2	Example Hookup to a MITEQ "MFS-xxx" STALO	2-34
2.5	RVP8 Custom Interfaces	2-35
2.5.1	Using the Legacy IFD Coax "Uplink"	2-35
3.	TTY Nonvolatile Setups	3-1
3.1	Overview of Setup Procedures	3-1
3.1.1	Factory, Saved, and Current Settings	3-2
3.1.2	V — View Card and System Status	3-3
3.2	View/Modify Dialogs	3-6
3.2.1	Mc — Top Level Configuration	3-6
3.2.2	Mp — Processing Options	3-8
3.2.3	Mf — Clutter Filters	3-12

3.2.4	Mt — General Trigger Setups	3-14
3.2.5	Mt<n> — Triggers for Pulsetwidth #n	3-17
3.2.5.1	Special Options for Tx Synthesis	3-21
3.2.6	Mb — Burst Pulse and AFC	3-24
3.2.6.1	AFC Motor/Integrator Option	3-31
3.2.7	M+ — Debug Options	3-32
3.2.8	Mz — Transmissions and Modulations	3-34
3.3	Advanced Options	3-35
3.3.1	* — Sample current noise levels	3-35
3.3.2	@ — Display/Change current Major Mode	3-35
3.3.3	~ — Burst-In / IF-In Swap Command (Rev.D IFD)	3-35
4.	Plot-Assisted Setups	4-1
4.1	P+ — Plot Test Pattern	4-2
4.2	General Conventions Within the Plot Commands	4-3
4.3	Pb — Plot Burst Pulse Timing	4-5
4.3.1	Interpreting the Burst Timing Plot	4-5
4.3.2	Available Subcommands Within "Pb"	4-6
4.3.3	TTY Information Lines Within "Pb"	4-7
4.3.4	Recommended Adjustment Procedures	4-8
4.4	Ps — Plot Burst Spectra and AFC	4-10
4.4.1	Interpreting the Burst Spectra Plots	4-10
4.4.2	Available Subcommands Within "Ps"	4-12
4.4.3	TTY Information Lines Within "Ps"	4-14
4.4.4	Computation of Filter Loss	4-16
4.4.5	Recommended Adjustment Procedures	4-19
4.5	Pr — Plot Receiver Waveforms	4-22
4.5.1	Interpreting the Receiver Waveform Plots	4-22
4.5.2	Available Subcommands Within "Pr"	4-24
4.5.3	TTY Information Lines Within "Pr"	4-25
4.6	Pa — Plot Tx Waveform Ambiguity	4-27
4.6.1	Interpreting the Ambiguity Plots	4-27
4.6.2	Available Subcommands Within "Pa"	4-29
4.6.3	TTY Information Lines Within "Pa"	4-30
4.6.4	Bench Testing of Compressed Waveforms	4-32
5.	Processing Algorithms	5-1
5.1	IF Signal Processing	5-4
5.1.1	FIR (Matched) Filter	5-4
5.1.2	RVP8/Rx Receiver Modes	5-5
5.1.2.1	Discussion of Halfband Filtering Modes 3-5	5-6
5.1.2.2	Discussion of Wide Dynamic Range Mode-4	5-7
5.1.3	Automatic Frequency Control (AFC)	5-9

5.1.4	Burst Pulse Tracking	5-9
5.1.5	Interference Filter	5-10
5.1.6	Large-Signal Linearization	5-13
5.1.7	Correction for Tx Power Fluctuations	5-13
5.2	Time Series ("I" and "Q") Signal Processing	5-15
5.2.1	Time Series Processing Overview	5-15
5.2.2	Frequency Domain Processing- Doppler Power Spectrum	5-17
5.2.3	Autocorrelations	5-20
5.2.4	Angle Synchronization	5-21
5.2.5	Clutter Filtering Approaches	5-21
5.2.5.1	Fixed Width Clutter Filters	5-23
5.2.5.2	Variable Width Clutter Filter	5-24
5.2.5.3	Gaussian Model Adaptive Processing (GMAP)	5-25
5.2.6	Range averaging and Clutter Microsuppression	5-32
5.2.7	Reflectivity	5-32
5.2.8	Velocity	5-34
5.2.9	Spectrum Width Algorithms	5-34
5.2.10	Signal Quality Index (SQI threshold)	5-35
5.2.11	Clutter Correction (CCOR threshold)	5-36
5.2.12	Weather Signal Power (SIG threshold)	5-37
5.2.13	Signal to Noise Ratio (LOG threshold)	5-37
5.3	Thresholding	5-38
5.3.1	Threshold Qualifiers	5-38
5.3.2	Adjusting Threshold Qualifiers	5-39
5.3.3	Speckle Filters	5-40
5.4	Reflectivity Calibration	5-44
5.4.1	Plot Method for Calibration of I_o	5-44
5.4.2	Single-Point Direct Method for Calibration of I_o	5-45
5.4.3	Treatment of Losses in the Calibration	5-46
5.4.4	Determination of dBZ_o	5-47
5.5	Dual PRT Processing Mode	5-49
5.5.1	DPRT-1 Mode	5-49
5.5.2	DPRT-2 Mode	5-50
5.6	Dual PRF Velocity Unfolding	5-51
5.7	Random Phase 2nd Trip Processing	5-55
5.7.1	Overview	5-55
5.7.2	Algorithm	5-55
5.7.3	Tuning for Optimal Performance	5-56
5.8	Signal Generator Testing of the Algorithms	5-60
5.8.1	Linear Ramp of Velocity with Range	5-60
5.8.2	Verifying PHIDP and KDP	5-61
5.8.3	Verifying RHOH, RHOV, and RHOHV	5-61

6. Host Computer Commands	6-1
6.1 No-Operation (NOP)	6-2
6.2 Load Range Mask (LRMSK)	6-2
6.3 Setup Operating Parameters (SOPRM)	6-4
6.4 Interface Input/Output Test (IOTEST)	6-11
6.5 Interface Output Test (OTEST)	6-12
6.6 Sample Noise Level (SNOISE)	6-12
6.7 Initiate Processing (PROC)	6-14
6.8 Load Clutter Filter Flags (LFILT)	6-23
6.9 Get Processor Parameters (GPARM)	6-25
6.10 Load Simulated Time Series Data (LSIMUL)	6-35
6.11 Reset (RESET)	6-37
6.12 Define Trigger Generator Waveforms (TRIGWF)	6-38
6.13 Define Pulse Width Control and PRT Limits (PWINFO)	6-39
6.14 Set Pulse Width and PRF (SETPWF)	6-40
6.15 Load Antenna Synchronization Table (LSYNC)	6-41
6.16 Set/Clear User LED (SLED)	6-43
6.17 TTY Operation (TTYOP)	6-43
6.18 Load Custom Range Normalization (LDRNV)	6-45
6.19 Read Back Internal Tables and Parameters (RBACK)	6-46
6.20 Pass Auxiliary Arguments to Opcodes (XARGS)	6-47
6.21 Load Clutter Filter Specifications (LFSPECS)	6-48
6.22 Configure Ray Header Words (CFGHDR)	6-49
6.23 Configure Interference Filter (CFGINTF)	6-50
6.24 Set AFC level (SETAFC)	6-50
6.25 Set Trigger Timing Slew (SETSLEW)	6-51
6.26 Hunt for Burst Pulse (BPHUNT)	6-51
6.27 Configure Phase Modulation (CFGPHZ)	6-52
6.28 Set User IQ Bits (UIQBITS)	6-52
6.29 Set Individual Thresholds (THRESH)	6-53
6.30 Set Task Identification Information (TASKID)	6-54
6.31 Define PRF "Pie Slices" (PRFSECT)	6-55
6.32 Configure Target Simulator (TARGSIM)	6-56
6.33 Set Burst Pulse Processing Options (BPOPTS)	6-57
6.34 Custom User Opcode (USRINTR and USRCONT)	6-58
A. Serial Status Formats	A-1
B. Optional Dual Polarization- ZDR, PHIDP, KDP, LDR, ...	B-1
B.1 Overview of Dual Polarization	B-1
B.2 Radar System Considerations	B-3
B.3 RVP8 Dual-Channel Receiver Approach	B-5

B.4	Overview of Processing Algorithms	B-6
B.5	Case 1: Fixed Transmit: Dual-Channel Receiver	B-9
B.6	Case 2: Simultaneous Dual Transmit and Receive (STAR)	B-10
B.7	Case 3: Alternating H/V Transmit: Single Receiver	B-11
B.8	Case 4: Alternating H/V Transmit: Dual Receiver	B-12
B.9	KDP Calculation	B-13
B.10	Standard Moment Calculations (T, Z, V, W)	B-14
B.11	Thresholding of Polarization Parameters	B-24
B.12	Calibration Considerations	B-25
C.	RVP8/RCP8 Packaging	C-1
C.1	Main Chassis General Description	C-2
C.1.1	Main Chassis Front Panel	C-7
C.1.2	Main Chassis Back Panel	C-8
C.1.3	Main Chassis Back Panel Power Section	C-9
C.1.4	Main Chassis Back Panel PC I/O Section	C-10
C.1.5	Main Chassis Back Panel PCI Card Section	C-11
C.2	I/O-62 and Connector Panel	C-14
C.3	IFD Module (RVP8 Only)	C-30
C.4	DAFC Module (RVP8 only)	C-33
D.	Installation and Test Procedure	D-1
D.1	Installation Check	D-3
D.2	Power-Up Check	D-4
D.3	Setup Terminal	D-5
D.4	Setup "V" Command (Internal Status)	D-6
D.5	Setup "Mc" Command (Board Configuration)	D-7
D.6	Setup "Mp" Command (Processing Options)	D-8
D.7	Setup "Mf" Command (Clutter Filters)	D-9
D.8	Setup "Mt" Command (General Trigger Setup)	D-10
D.9	Initial Setup of Information for Each Pulse Width	D-11
D.10	Setup "Mb" Command (Burst Pulse and AFC)	D-12
D.11	Setup "M+" Command (Debug Options)	D-13
D.12	Setup "Mz" Command (Transmitter Phase Control)	D-14
D.13	A-Scope Test	D-15
D.14	Burst Pulse Alignment	D-16
D.15	Bandwidth Filter Adjustment	D-17
D.16	Digital AFC (DAFC) Alignment (Optional)	D-18
D.17	Analog AFC Voltage Alignment (Optional)	D-19
D.18	MFC Functional Test and Tuning (Optional)	D-21
D.19	AFC Functional Test (Optional)	D-22
D.20	Input IF Signal Level Check	D-23
D.21	Dynamic Range Check	D-24

D.22 Receiver Bandwidth Check	D-26
D.23 Receiver Phase Noise Check	D-28
D.24 Hardcopy and Backup of Final Setups	D-29
D.25 IFD Stand-alone SigGen Bench Test	D-30
D.26 RVP8/Tx Stand-alone Bench Test	D-31
D.27 RVP8/Rx Stand-alone Bench Test	D-32
E. RVP8 Developer's Notes (draft)	E-1
E.1 Organization of the RDA Software	E-1
E.2 RVP8 Overall Code Organization	E-2
E.2.1 RVP8 Software Maintenance Model	E-3
E.2.2 Installing Incremental RDA Upgrades	E-3
E.2.3 Rebuilding the RDA Linux Kernel Module	E-4
E.3 Debugging and Profiling Your Code	E-5
E.3.1 Monitoring Opcode/Data Activity: <code>-exposeIO</code>	E-5
E.3.2 Showing Live Acquired Pulse Info: <code>-showAQ</code>	E-6
E.3.3 Showing Coherent Processing Intervals: <code>-showCPIs</code>	E-7
E.3.4 Showing RealTime Callback Timers: <code>-showRTCtrl</code>	E-7
E.3.5 Using <code>ddd</code> on the Main & Proc Code	E-8
E.3.6 Finding memory leaks with <code>valgrind</code>	E-9
E.3.7 Profiling with <code>gprof</code>	E-9
E.4 Creating New Major Modes from Old Ones	E-10
E.4.1 Function Pointers are the Key to Customization	E-10
E.5 Real-Time Control of the RVP8	E-12
E.5.1 Using the Programmable Callback Timers	E-12
E.5.2 Example: Standard Trigger/Antenna Events	E-12
E.5.3 Example: RealTime Interrupt Histogram	E-13
E.6 Customizing the (I,Q) Data Stream	E-14
E.6.1 Defining the FIR Matched Filter	E-14
E.6.2 Applying Raw Pulse Corrections	E-14
E.6.3 Inserting UserIQ Header BIts	E-14
E.7 Customizing the Front Panel Display	E-14
E.8 Adding Custom DSP/Lib Opcodes	E-14
E.9 Using the Softplane for Physical I/O	E-14
E.9.1 Softplane Programmer's Model	E-14
E.9.2 Reducing Unnecessary PCI Traffic	E-15
E.10 Handling Live Antenna Angles	E-15
E.11 Creating Custom Trigger Sequences	E-15
E.11.1 Defining Trigger Waveshapes	E-15
E.11.2 Defining Trigger PRT Sequences	E-15
E.11.3 Polarization and Phase Control	E-15
E.11.4 Example: Adding PRT Micro-Stagger	E-15

E.12	Determining CPI's and Ray Boundaries	E-16
E.13	Using the RVP8 TimeSeries API	E-16
E.13.1	Reader and Writer Clients	E-16
E.13.2	Attach/Detach Details	E-17
E.13.3	Extracting Pulses via Sequence Numbers	E-17
E.13.4	Using Memory Bandwidth Effectively	E-17
E.13.5	Packed and Floating Data Formats	E-17
E.14	Using the Intel IPP Library	E-17
F.	Time Series Recording	F-1
F.1	Overview	F-1
F.2	TS Record/Playback Software Architecture	F-2
F.2.1	General Architecture	F-2
F.2.2	Description of Processes	F-2
F.3	Installation & Configuration	F-4
F.3.1	Required Software	F-4
F.3.2	Configuring UDP Ports	F-4
F.3.3	Configuring automatic start-up of tsimport & tsexport	F-4
F.3.4	Configuring Network buffering for tsimport	F-5
F.3.5	Tsimport and Tsexport from the command line	F-5
F.4	Tsswitch Utility	F-6
F.5	Tsarchive Utility	F-7
F.5.1	Archive Directory Area	F-7
F.5.2	TS Source	F-8
F.5.3	Filter	F-9
F.5.4	TS Archive Log Area	F-10
F.6	Specific Software Application Examples	F-12
F.6.1	Case 1: TS recording on a local RVP8	F-13
F.6.2	Case 2: TS recording on separate archive host	F-14
F.6.3	Case 3: TS playback on a local RVP8	F-15
F.6.4	Case 4: TS playback from a separate archive host to an RVP8	F-16
F.6.5	Quick Guides	F-17
F.7	Ascope Playback Features	F-18
F.8	TS Playback using IRIS	F-20
F.9	TS Viewing Utility (tsview)	F-21
F.9.1	Overview	F-21
F.9.2	Starting tsview and Sample Session	F-21
F.9.3	Tsview Command Line Options	F-22
F.10	TS Record Data Format	F-25
G.	References and Credits	G-1
Index	Index-1

Figures

Figure 1-1:	Analog vs Digital Receiver for Magnetron Systems	1-19
Figure 1-2:	Analog vs Digital Receiver for Klystron Systems	1-20
Figure 1-3:	IF to I/Q Processing Steps	1-23
Figure 1-4:	I/Q Processing for Weather Moment Extraction	1-26
Figure 1-5:	Network Architecture for Socket Interface with DspExport	1-34
Figure 2-1:	Calibration Plot for a Stand-alone 14-Bit IFD	2-10
Figure 2-2:	Tradeoff Between Dynamic Range and Sensitivity	2-11
Figure 2-3:	Assembly Diagram of the DAFC	2-30
Figure 2-4:	Recommended Receiving Circuit for the Coax Uplink	2-35
Figure 2-5:	Timing Diagram of the IFD Coax Uplink	2-36
Figure 4-1:	The Test Pattern Display	4-2
Figure 4-2:	Successful Capture of the Transmit Burst	4-5
Figure 4-3:	Example of a Filter With Excellent DC Rejection	4-10
Figure 4-4:	Example of a Poorly Matched Filter	4-19
Figure 4-5:	Example of a Filter With Poor DC Rejection	4-21
Figure 4-6:	Example of Combined IF Sample and LOG Plot	4-22
Figure 4-7:	Example of a Noisy High Resolution "Pr" Spectrum	4-24
Figure 4-8:	Ambiguity Diagram of a Compressed Tx Pulse	4-27
Figure 4-9:	Frequency, Phase and Amplitude of a Compressed Tx Pulse	4-28
Figure 4-10:	IFD Sampling of Optimized Compressed Tx Waveform	4-32
Figure 4-11:	Ideal and Actual Linear-FM Spectrum Displayed in Ps Plot	4-33
Figure 5-1:	Flow Diagram of RVP8 Processing	5-3
Figure 5-2:	Linearization of Saturated Signals Above +4.5dBm (Rev B/C IFD) .	5-13
Figure 5-3:	Example of time series and Doppler power spectrum	5-16
Figure 5-4:	Typical form of a time series window	5-18
Figure 5-5:	Impulse response of a typical window	5-19
Figure 5-6:	Example of fixed width	5-23
Figure 5-7:	Variable Width Clutter Filter	5-24
Figure 5-8:	GMAP Algorithm Steps	5-26
Figure 5-9:	GMAP example	5-31
Figure 5-10:	Model Intensity Curve	5-44
Figure 5-11:	Illustration of Losses that Affect LOG Calibration	5-47
Figure 5-12:	Dual PRF Concepts	5-52
Figure 5-13:	Example of Dual PRF Trigger Waveforms	5-54
Figure 5-14:	Random Phase Processing Algorithm	5-59
Figure B-1:	Least Squares KDP calculation	B-13
Figure C-1:	Main Chassis- Front Panel	C-3
Figure C-2:	Main Chassis- Back Panel	C-4
Figure C-3:	Main Chassis- Right Side View	C-5
Figure C-4:	Main Chassis Internal Cabling	C-6

Figure C-5:	RVP8 I/O-62 Connector Panel	C-16
Figure C-6:	RCP8 I/O-62 Connector Panel	C-17
Figure C-7:	RVP8/IFD Module	C-31
Figure C-8:	IFD Front Panel	C-32
Figure C-9:	View of DAFC Module	C-33

Tables

Table 1-1: Examples of Dual PRF Velocity Unfolding	1-28
Table 2-1: Differences Among Versions of the IFD	2-3
Table 2-2: IFD Connectors (All Revisions)	2-5
Table 2-3: IFD Connectors (Rev.A-Rev.D)	2-5
Table 2-4: IFD Connectors (Rev.E & Greater)	2-5
Table 2-5: IFD Toggle Switch Settings	2-6
Table 2-6: IFD LED Indicator Interpretations	2-6
Table 2-7: IFD Internal Jumper Settings	2-7
Table 2-8: Clock Locking Component Options	2-19
Table 2-9: Direct Connections to RVP8 Main Chassis	2-21
Table 2-10: DAFC Protocol Jumper Selections	2-31
Table 2-11: Pinout for the CTI "MVSr-xxx" STALO	2-33
Table 2-12: Bit Assignments for the IFD Coax Uplink	2-36
Table 5-1: Algebraic Quantities Within the RVP8 Processor	5-2
Table 5-2: Algorithm Results for +16dB Interference	5-11
Table 5-3: Algorithm Results for +26dB Interference	5-12
Table 6-2: RVP8 Status Output Words	6-26
Table A-1: Internal BITE Packet (RVP8 to Host)	A-1
Table A-2: Internal QBITE Packet (RVP8 to Host)	A-5
Table B-1: Transmitter Types	B-3
Table B-2: Supported Polarization Modes and Outputs	B-6
Table C-1: RVP8 and RCP8 I/O-62 Card Jumper Settings	C-12
Table C-2: RVP8/Rx Card Jumper Settings	C-13
Table C-3: RVP8/Tx Card Jumper Settings	C-13
Table C-4: J1 "AZ INPUT"	C-18
Table C-5: J2 "AZ OUTPUT"	C-19
Table C-6: J3 RVP8: "PHASE OUT"; RCP8 "CONTROL"	C-20
Table C-7: J4 "EL INPUT"	C-21
Table C-8: J5 "EL OUTPUT"	C-22
Table C-9: J6 "RELAY"	C-23
Table C-10: J7: RVP8 "SPARE"; RCP8 "BITE 19:0"	C-24
Table C-11: J8: RVP8 "SPARE"; RCP8 "ANALOG IN"	C-25
Table C-12: J9 RVP8: "MISC I/O" ; RCP8: "PED/STATUS"	C-26
Table C-13: J10 "SERIAL"	C-27
Table C-14: J11 "SERIAL"	C-27
Table C-15: J12 "S-D"	C-28
Table C-16: RVP8 BNC Connector Pin Assignments	C-29
Table C-17: RCP8 BNC Connector Pin Assignments	C-29
Table F-1: TS File Format	F-25