

Index

A

AGC, definition, A-1
Alternating polarization, 6-7
Antenna/Transmitter status area, Radar Status menu, 4-9
Archive menu, definition, A-1
Associated TASK, definition, A-1
Automatic Mode Switch menu, 4-14
AZ/EL Display, Real Time Display, 8-5

B

BEAM product, definition, A-1

C

CAPPI product, definition, A-1
Clutter-to-signal ratio. *See* CSR
Color Scale, Real Time Display menu, 8-7
Commands, pull-down menu, 2-7
COMP product, definition, A-1
Config, Real Time Display menu, 8-3
Configuring output, Real Time Display, 8-8
Connect pull-down menu, IRIS menu bar, 2-4
Contents command, Help pull-down menu, 2-7
Corrected Velocity, definition, A-7
CSR threshold
 level, 6-16
 parameter, 6-15

D

Data parameter, abbreviations, A-10
Data Selection, Real Time Display, 8-5
dBT, definition, A-1
dBZ, definition, A-1
dBZc, definition, A-1

Description field, TASK Configuration menu, 6-3
Differential reflectivity. *See* ZDR
Doppler signal processor, in Radar Status menu, 4-8
Doppler spectrum, definition, A-2
Doppler spectrum width, definition, A-2
DSP field, Radar Status menu, 4-8

F

FFT mode, TASK Configuration menu, 6-13

H

Help pull-down menu, 2-7
 viewing online documentation, 2-12
Hybrid TASK, 1-8 , 7-1
 naming convention, 6-3 , 7-6
 Start, Stop, and Repeat times, 7-4
Hybrid Task, definition, A-2

I

Index command, Help pull-down menu, 2-7
Ingest file, definition, A-2
Ingest process, 1-8
Ingest Summary menu, definition, A-2
INU, definition, A-2
IRIS, definition, A-2
Iris command, 1-12 , 2-1
IRIS menu bar, 1-12 , 2-1
 definition, A-2
IRIS/Analysis system, 1-2
IRIS/Display system, 1-2
IRIS/Radar system, 1-2
IRISnet, 3-1

K

KDP, definition, A-2

L

LOG receiver, threshold level, TASK Configuration menu, 6-15

M

- Mandatory field, setting priority of TASK, 7–8
- Manual scan
 - definition, A–3
 - scheduling and running, 7–10
- Manuals, 2–12
- MAX product, A–3
- Menu, user access restrictions, 1–11
- Menus command, IRIS menu bar, 2–5
- Message List menu, menu format, 5–3
- Message popup, 5–2
- Messages field, Radar Status menu, 4–6
- Mode switching, 4–13
- MONITOR mode, B–1
 - MONITOR TASK Schedule, B–8
 - Product Output menu, B–10
 - Radar Status menu, B–8
 - setting up MONITOR TASKS, B–4
 - testing, B–10
- Month abbreviations, A–9

N

- NDOP product, definition, A–3
- Network Receiver field, Radar Status Menu, 4–7
- Network Status menu, in Radar Status menu, 4–6
- NORDRAD field, Radar Status menu, 4–6

O

- Observer
 - access to menus, 1–11
 - default password, 1–16
- On Menu command, Help pull-down menu, 2–7
- Operator
 - access to menus, 1–11
 - default password, 1–16
- Output Schedule field, Radar Status menu, 4–6
- Overlays, Real Time Display menu, 8–5

- Overview, Real Time Display, 8–8

P

- Passive IRIS, C–1
 - hardware, C–1
 - overview, C–1
 - scheduling and running, 7–11
 - setup, C–3
 - Task Scheduling, C–4
 - testing, C–5
- PhiDP, definition, A–3
- PhiH, definition, A–3
- PhiV, definition, A–3
- PP02, A–3
- PPI Full scan
 - definition, A–3
 - resolution, 6–5
- PPI product, definition, A–3
- PPI Sector scan
 - azimuth and elevation, 6–4
 - definition, A–3
 - resolution, 6–5
- PPP mode, TASK Configuration menu, 6–13
- PRF, definition, A–4
- Printing, File pull-down menu, 2–6
- Product, definition, A–4
- Product Configuration menu, definition, A–4
- Product Generation field, Radar Status menu, 4–5
- Product Generator process, 1–9
- Product Output field, Radar Status menu, 4–7
- Product Output menu
 - definition, A–4
 - MONITOR mode example, B–10
- Product Output process, 1–9
- Product Schedule field, Radar Status menu, 4–5
- Product Scheduler menu, definition, A–4
- Protected areas, definition, A–4

Q

- Qiris command, 1–17

R

- R, definition, A-4
- Radar control processor. *See* RCP
- Radar process, 1-8
- Radar Process field, Radar Status menu, 4-3
- Radar Status menu, 4-1
 - Control Section, 4-3
 - definition, A-4
 - menu format
 - Antenna/Transmitter Status, 4-9
 - Subsystem Status, 4-8
 - MONITOR mode example, B-8
 - running IRIS from, 4-12
 - switching configurations automatically, 4-14
- Radar TASK, 6-1
- Radiate field, Radar Status menu, 4-5
- Rainfall rate, definition, A-4
- Random phase mode, TASK Configuration menu, 6-13
- Range, maximum, Real Time Display, 8-5
- Ranges, Real Time Display menu, 8-3
- RAW product, definition, A-4
- RCP, 1-3
 - reset from RST menu, 4-3
 - status on RST menu, 4-8
- Real Time Display, 8-1
 - menu features, 8-2
- Real time display, definition, A-5
- Real Time Display field, Radar Status menu, 4-7
- Real Time Display process, 1-9
- Reflectivity, definition, A-5
- Reingest field, Radar Status menu, 4-5
- Repeats field, Message List menu, 5-3
- Reset Size command, 2-7
- RHI, Real Time Display menu, 8-3
- RHI product, definition, A-5
- RHI scan
 - azimuth and elevation, 6-4
 - resolution, 6-5
- RHI TASK configuration, B-6
- RHI velocity algorithm, 6-6
- RHOH, definition, A-5
- RHOHV, definition, A-5

- RHOV, definition, A-5
- RVP6, definition, A-5
- RVP7, definition, A-6

S

- Scan Mode field, TASK Configuration menu, 6-4
- Server, connecting and disconnecting, 2-4
- Server menu, 2-2
- Servo Power field, Radar Status menu, 4-5
- Set Colors, Real Time Display menu, 8-3
- setup utility, Real Time Display, 8-8
- SHEAR product
 - configuration example. *See* TDWY mode definition, A-6
- Shutdown procedure, 1-17
- SIG threshold
 - level, 6-16
 - parameter, 6-15
- Signal processor
 - definition, A-6
 - noise sample, 4-3
 - supported by IRIS, 1-3
- Siris command, 1-16
- Site ID, Real Time Display menu, 8-4
- Site Status field, Radar Status menu, 4-6
- SLINE product, definition, A-6
- SNR, 6-9
- Speckle filter, TASK Configuration menu, 6-17
- Spectrum width, definition, A-7
- Speech, setup menu, 2-9
- SQI, definition, A-6
- SQI threshold, 6-15
 - parameter, 6-15
- Status LED, Real Time Display menu, 8-4
- SURVEILLANCE TASK configuration, B-5

T

- T, definition, A-1
- T/R Power field, Radar Status menu, 4-5
- Target Detection, 6-13
- TASK
 - configuration, 1-8

- definition, A-6
- naming conventions, 6-3
- priority of, 7-8
- TASK Configuration menu, 6-1
 - Antenna/Radar Control, 6-4
 - clutter filters, 6-10
 - Data Quality Thresholding, 6-14
 - definition, A-6
 - MONITOR mode example, B-4
 - obtaining high quality data, 6-18
 - Processor Configuration, 6-8
 - scan speed, 6-6
 - SNR output, 6-9
 - TASK names and descriptions, 6-3
- TASK Schedule field, Radar Status menu, 4-3
- TASK Scheduler menu, 7-1
 - adding, editing, removing TASKS, 7-6
 - definition, A-6
 - menu format, 7-2
 - MONITOR mode example, B-8
 - passive IRIS, 7-11
 - running and stopping a TASK, 7-7
 - scheduling and running manual scans, 7-10
- scheduling automatic TASKS, 7-8
- TDWR mode, B-1
- Terminal Doppler Weather Radar. *See* TDWR mode
- Threshold Level field, TASK Configuration menu, 6-16
- Thresholding, in TCO menu, 6-14-6-17
- Time, Real Time Display, 8-4
- Time field, Message List menu, 5-3
- TOPS product, definition, A-6
- TRACK product, definition, A-7

U

- Update Now command, Commands
 - pull-down menu, 2-7

V

- V, definition, A-7
- V data parameter, 1-8
- Vc, definition, A-7
- Velocity, definition, A-7
- VIL product, definition, A-7
- VVP product, definition, A-7

W

- W, definition, A-7
- W data parameter, 1-8
- WARN product, definition, A-7
- Watchdog process, 1-10
- Weather monitoring, configuration example, B-1
- Width, definition, A-7
- WIND product, definition, A-7
- Window output device, 1-10 , 1-14
 - fixing problems, 5-5
- Workstation, supported by IRIS, 1-3

X

- X-Window display. *See* Window Output Device
- XSECT product, definition, A-8

Z

- Z
 - data parameter, 1-8
 - definition, A-1 , A-8
- Zc, definition, A-1 , A-8
- ZDR
 - data parameter, 1-8
 - definition, A-8
- ZT, data parameter, 1-8