

Index

A

A/D input, C-25
Acquisition clock, TTY setup, 3-6
AFC
 algorithms, 5-9
 analog, 2-15
 digital, from DAFC, 2-30
 introduction, 1-31
 TTY setup, 3-26
Angle
 input, 2-23
 output, 2-23
 S/D input, 2-24
Angle synchronization, introduction, 1-27
Angle syncing, LSYNC command, 6-42
Autocorrelations
 algorithms, 5-20
 introduction, 1-26
Automatic Frequency Control. *See* AFC
Azimuth angle, C-18 , C-19 , C-28

B

Back panel, C-8
BITE serial format, A-1 , A-5
Burst pulse
 algorithms, 5-9
 introduction, 1-22

C

Calibration, introduction, 1-11
CCOR threshold
 algorithms, 5-36
 qualifier, 5-38
CFGINTF command, 6-50
Chassis
 connector panel, 2-22
 direct connections, 2-21
 installation, 2-20
Clutter correction. *See* CCOR

Clutter filter
 LFILT command, 6-23
 microsuppression
 algorithms, 5-32
 TTY setup, 3-8
Clutter filtering, 5-21
Coax uplink
 installation, 2-17
 specification, 2-35
COHO, introduction, 1-14
Configuration examples
 dual polarization, 1-7
 Klystron, 1-5
 magnetron, 1-4
Connector panel, C-14
Control, introduction, 1-31
Corrected reflectivity, introduction, 1-30
Correction for Tx Power, algorithms, 5-13

D

DAFC
 CTI STALO example, 2-32
 description, 2-30
 drawings, pin out, C-33
 jumpers, 2-31
 MITEQ STALO example, 2-34
Debug Options, TTY setup, 3-32
Developer's Notes, E-1
DFT, 5-17
DFT/FFT, introduction, 1-29
Diagnostics
 introduction, 1-32
 TTY setup, 3-4
Differential phase. *See* PhiDP
Differential reflectivity. *See* ZDR
Digital receiver, introduction, 1-17
DspExport, 1-34
Dual polarization
 algorithms, B-1
 calibration, B-25
 dual channel receiver, B-5
 introduction, 1-7 , 1-30
 KDP calculation, B-13
 modes, B-6
 notation, B-6

- radar systems, B-3
- signal generator tests, 5-61
- standard moments, B-14
- thresholding, B-24
- Dual polarization , modes
 - alternating dual channel, B-12
 - alternating single channel, B-11
 - fixed transmit, B-9
 - simultaneous transmit, B-10
- Dual PRF. *See* Velocity unfolding
- Dual PRT. *See* Velocity unfolding

E

- Elevation angle, C-21 , C-22 , C-28
- ENDRAY_ output, introduction, 1-28
- Environment, 1-44

F

- Features
 - digital transmitter, 1-1
 - open hardware and software, 1-2
 - frequency agility, 1-14
 - I/Q LAN output, 1-3
 - LAN connection, 1-3
 - pulse compression, 1-14
 - SoftPlane, 1-2
- FFT, 5-17
 - introduction, 1-29
- Fiber optic downlink, installation, 2-17
- FIFO, output, 6-1
- FIR filter
 - algorithms, 5-4
 - TTY setup, 3-19
- Front panel display, 2-26

G

- Gaussian model filter, *see* GMAP, 5-25
- Get processor parameters, GPARM command, 6-25
- GMAP
 - algorithm steps, 5-25
 - benefits, 5-25
 - configuration, 5-29

- example, 5-29
- model assumptions, 5-25
- GPARM, command, 6-25

H

- History, 1-1
- Host computer interface
 - complete command list, 6-1
 - socket, 2-27

I

- I/O-62
 - connector panel
 - drawings, C-14
 - pin out, C-14
 - connector panel, 2-22
 - introduction, 1-15
- I/Q, introduction, 1-3 , 1-30
- IF
 - bandwidth, 2-9
 - frequency selection
 - installation, 2-14
 - TTY setup, 3-24
 - IF to I/Q processing , 1-23
 - saturation, 2-8
 - signal processing, 1-21 , 5-4
- IFD
 - adjustment, 2-6
 - drawings, C-30
 - dynamic range, 2-9
 - I/O connections, 2-5
 - input power, 1-44 , 2-1 , 2-4
 - installation, 2-2
 - introduction, 1-9
 - LED indicators, 2-6
 - mounting, 2-4
 - reference clock, 2-15
 - revision history, 2-3
 - sampling clock, 1-21
 - signal level, 2-11
- Initiate processing, PROC command, 6-14
- Installation, test procedure, D-1
- Intel IPP library, E-18
- Interference Filter
 - algorithms, 5-10

CFGINTF command, 6–50
Intermediate frequency. *See* IF
IOTEST command, 6–11

K

KDP
algorithm. *See* Dual Polarization
description, B–1
Kernel Module, E–5
Klystron
example, 1–20
introduction, 1–5

L

Large–signal linearization, algorithms, 5–13
LDR
algorithm. *See* Dual polarization
description, B–2
LDRNV command, 6–45
LEDs
on IFD, 2–6
SLED command, 6–44
LFILT command, 6–23
LOG filter, threshold qualifier, 5–38
LOG threshold, algorithms, 5–37
LRMSK command, 6–2
LSIMUL command, 6–36
LSYNC command, 6–42

M

Magnetron
example, 1–18
introduction, 1–4
Main chassis
back panel, C–8
drawings, C–2
general description, C–2
input power, 1–44 , 2–1 , 2–20 , C–7 , C–9
PC I/O, C–10
PCI cards, C–11
Mean velocity. *See* Velocity
Motherboard, introduction, 1–13

N

Network, socket interface, 2–27
Network interface, 1–34 , 1–35
Noise sample, SNOISE command, 6–12
NOP command, 6–2

O

Optional argument list, XARGS command,
6–47
OTEST command, 6–12

P

Phase control
output, 2–23
TTY setup, 3–34
PhiDP
algorithm. *See* Dual Polarization
description, B–1
Power requirements, 2–1 , 2–20 , C–7 , C–9
Power requirements, 1–44
Power-up, 2–26
PRF
limits, PWINFO command, 6–39
SETPWF command, 6–41
TTY setup, 3–14 , 3–18
PROC command, 6–14
Pulse compression, introduction, 1–14
Pulse pair, introduction, 1–29
Pulsewidth control
introduction, 1–31
PWINFO command, 6–39
SETPWF command, 6–41
TTY setup, 3–14
PWINFO command, 6–39

R

R2 processing, TTY setup, 3–8
Random phase
algorithms, 5–55
introduction, 1–30
Range averaging
algorithms, 5–32
introduction, 1–27

- LRMSK command, 6–3
- Range mask, load command (LRMSK), 6–2
- Range normalization, LDRNV command, 6–45
- Range resolution, TTY setup, 3–19
- Range unfolding, introduction, 1–30
- RBACK command, 6–46
- Real time TTY, TTY setup, 3–33
- Receiver Modes, algorithms, 5–5
- Reflectivity
 - algorithms, 5–32
 - introduction, 1–30
- Reflectivity calibration, 5–44
- Relays, C–23
- Reliability, 1–44
- RESET command, 6–38
- RhoHV, description, B–2
- ROM revision, TTY setup, 3–3
- Round-trip delay, TTY setup, 3–4
- RVP8/Rx card, introduction, 1–10
- RVP8/Tx card, introduction, 1–13

S

- S/D input, C–28
- Saturation headroom, TTY setup, 3–9
- SBC, introduction, 1–13
- Self tests, 1–32
- Serial status formats, A–1
- SETPWF command, 6–41
- SIG threshold, algorithms, 5–37
- Simulations
 - burst pulse, TTY setup, 3–30
 - LSIMUL command, 6–36
 - output data, TTY setup, 3–32
- SLED command, 6–44
- SNOISE command, 6–12
- Socket interface, 1–34 , 1–35 , 2–27
- Software, support utilities, 1–33
- SOPRM command, 6–4
- Speckle filter
 - algorithms, 5–40
 - introduction, 1–28
- Spectrum Processing
 - clutter , 5–21

- window, 5–17
- Spectrum processing, 5–17
- Spectrum width
 - algorithms, 5–34
 - introduction, 1–30
- SQI threshold
 - algorithms, 5–35
 - qualifier, 5–38
- STAR, B–10
- Synchro input, C–28

T

- TAG lines
 - introduction, 1–27
 - TTY setup, 3–10
- Test point, output , 2–24
- Testing
 - test procedure, D–1
 - with signal generator, 5–60
- Thresholding
 - algorithms, 5–38
 - adjusting, 5–39
 - introduction, 1–28
- Time series
 - algorithms, 5–15
 - API, E–17
- Trigger
 - blanking, 1–31
 - external input, TTY setup, 3–14
 - external pre-trigger, 2–22
 - input, 2–25
 - installation, 2–22 , 2–25
 - introduction, 1–31
 - output, 2–25
 - outputs, TRIGWF command, 6–38
 - TTY setup, 3–14
 - waveform, example of Dual PRF, 5–54
- TRIGWF command, 6–38
- TTY setup
 - complete listing, 3–1
 - M+ – debug options, 3–32
 - Mb – burst pulse and AFC, 3–24
 - Mc – top level configuration, 3–6
 - Mf – clutter filters, 3–12
 - Mp – processing options, 3–8

Mt – general trigger setups, 3–14
Mz – transmissions modulations, 3–34
P+ – plot test pattern, 4–2
Pb – plot burst pulse timing, 4–5
Pr – plot receiver waveforms, 4–22
Ps – plot burst spectra and AFC, 4–10
TTYOP command, 6–44
V – view internal status, 3–3
TTYOP command, 6–44
TWT, example, 1–20

U

Uncorrected reflectivity, introduction, 1–30
Unfolding, introduction. *See* Velocity unfolding

V

Velocity
algorithms, 5–34

introduction, 1–30
Velocity unfolding
algorithms, 5–49 , 5–51
introduction, 1–28

W

Weather signal processing, introduction, 1–25
WSP threshold, qualifier, 5–38

X

XARGS command, 6–47

Z

ZDR
algorithm. *See* Dual polarization
description, B–1