


# Release Notes

IRIS Focus  
Version 6.0



PUBLISHED BY

Vaisala Oyj  
Vanha Nurmijärventie 21, FI-01670 Vantaa, Finland  
P.O. Box 26, FI-00421 Helsinki, Finland  
+358 9 8949 1

Visit our Internet pages at [www.vaisala.com](http://www.vaisala.com).

© Vaisala 2021

No part of this document may be reproduced, published or publicly displayed in any form or by any means, electronic or mechanical (including photocopying), nor may its contents be modified, translated, adapted, sold or disclosed to a third party without prior written permission of the copyright holder. Translated documents and translated portions of multilingual documents are based on the original English versions. In ambiguous cases, the English versions are applicable, not the translations.

The contents of this document are subject to change without prior notice.

Local rules and regulations may vary and they shall take precedence over the information contained in this document. Vaisala makes no representations on this document's compliance with the local rules and regulations applicable at any given time, and hereby disclaims any and all responsibilities related thereto.

This document does not create any legally binding obligations for Vaisala towards customers or end users. All legally binding obligations and

agreements are included exclusively in the applicable supply contract or the General Conditions of Sale and General Conditions of Service of Vaisala.

This product contains software developed by Vaisala or third parties. Use of the software is governed by license terms and conditions included in the applicable supply contract or, in the absence of separate license terms and conditions, by the General License Conditions of Vaisala Group.

This product may contain open source software (OSS) components. In the event this product contains OSS components, then such OSS is governed by the terms and conditions of the applicable OSS licenses, and you are bound by the terms and conditions of such licenses in connection with your use and distribution of the OSS in this product. Applicable OSS licenses are included in the product itself or provided to you on any other applicable media, depending on each individual product and the product items delivered to you.

## Table of contents

<b>1.</b>	<b>About this document</b> .....	3
1.1	Version information.....	3
1.2	Related documents.....	3
1.3	Trademarks.....	3
<b>2.</b>	<b>IRIS Focus 6.0 release notes</b> .....	4
2.1	Release notices.....	4
2.2	Updates and fixes.....	4
2.3	Known issues.....	6
2.4	Upgrading IRIS Focus 5.0 or later to IRIS Focus 6.0.....	7
2.4.1	License.....	7
2.4.2	Running the upgrade.....	7
2.4.3	Updating user roles.....	10
2.5	Installation command options.....	10
<b>3.</b>	<b>IRIS Focus 5.3 release notes</b> .....	12
3.1	Release notices.....	12
3.2	Updates and fixes.....	13
3.3	Known issues.....	13
3.4	Upgrading IRIS Focus 4.0 or later to IRIS Focus 5.3.....	14
3.4.1	License.....	14
3.4.2	Running the upgrade.....	15
<b>4.</b>	<b>IRIS Focus 5.2 release notes</b> .....	19
4.1	Release notices.....	19
4.2	Updates and fixes.....	20
4.3	Known issues.....	22
4.4	Upgrading IRIS Focus 4.0 or later to IRIS Focus 5.3.....	22
4.4.1	License.....	23
4.4.2	Running the upgrade.....	23
<b>5.</b>	<b>IRIS Focus 5.1.1 Release Notes</b> .....	27
5.1	Release Notices.....	27
5.2	Fixes.....	27
5.3	Known Issues.....	28
<b>6.</b>	<b>IRIS Focus 5.1. Release Notes</b> .....	29
6.1	Release Notices.....	29
6.2	Updates and Fixes.....	29
6.3	Known Issues.....	30
6.4	Upgrading IRIS Focus 4.0 or 5.0 to IRIS Focus 5.1.....	31
<b>7.</b>	<b>IRIS Focus 5.0.1 Release Notes</b> .....	33
7.1	Release Notices.....	33
7.2	Fixes.....	33
7.3	Known Issues.....	34
7.4	Upgrading IRIS Focus 5.0 to IRIS Focus 5.0.1.....	34
<b>8.</b>	<b>IRIS Focus 5.0 Release Notes</b> .....	36
8.1	Release Notices.....	36
8.2	Updates and Fixes.....	36
8.3	Known Issues.....	38
8.4	Notes on Using IRIS Focus.....	39

<b>9. Backing up the data</b> .....	<b>40</b>
9.1 Making a manual back-up.....	40
9.2 Restoring from backup.....	40
<b>Technical support</b> .....	<b>43</b>
<b>Warranty</b> .....	<b>43</b>
<b>Recycling</b> .....	<b>43</b>

# 1. About this document

## 1.1 Version information

This document provides information on IRIS Focus releases.

Table 1 Document versions (English)

Document code	Date	Description
M211904EN-L	April 2021	For IRIS Focus 6.0
M211904EN-K	September 2020	For IRIS Focus 5.3.
M211904EN-J	July 2020	For IRIS Focus 5.2.

## 1.2 Related documents

Table 2 Related documents

Document code	Name
M211850EN	<i>IRIS Focus Administrator Guide</i>
M211849EN	<i>IRIS Focus User Guide</i>
M212545EN	<i>IRIS Focus Lightning Administrator Guide</i>
M212544EN	<i>IRIS Focus Lightning User Guide</i>
M211904EN	<i>IRIS Focus Release Notes</i>
M211315EN	<i>IRIS and RDA Software Installation Guide</i>

## 1.3 Trademarks

Vaisala® is a registered trademark and HydroClass™, IRIS™ and Total Lightning Processor™ are trademarks of Vaisala Oyj.

Chrome™ is a trademark of Google Inc.

Firefox® is a registered trademark of Mozilla Foundation.

Edge® is a trademark of Microsoft Corporation in the United States and other countries.

All other product or company names that may be mentioned in this publication are trade names, trademarks, or registered trademarks of their respective owners.

## 2. IRIS Focus 6.0 release notes

### 2.1 Release notices

Vaisala is pleased to announce the release of IRIS Focus 6.0.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

#### Upgrade to IRIS Focus 6.0

You can upgrade to IRIS Focus 6.0 from IRIS Focus 5.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 5.0 before you can upgrade to IRIS Focus 6.0.

When upgrading to 6.0, the maps and the terrain file will stay installed.



When you upgrade from IRIS Focus 5.x to 6.0, the data in Data Manager is not deleted.



The upgrade script takes a back-up of the webapp/config database and the config directory. If you need to back up other files, do a manual back-up. For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.

Table 3 System requirements

CentOS	IRIS Analysis/IRIS Radar	Total Lightning Processor (TLP)
IRIS Focus 6.0 has been tested with CentOS 7.4 and 7.6. IRIS Focus is also expected to work with other versions of CentOS 7.x.	The radar data visualization features of IRIS Focus 6.0 require IRIS Analysis/Radar 8.13.6 or later on the same network.  Note that IRIS Analysis must not be visible to the public Internet.	The lightning data visualization features of IRIS Focus require TLP v. 1.2.7 on the same network.

### 2.2 Updates and fixes

#### New features

- *Real-time lightning data visualization*  
IRIS Focus now enables the visualization of lightning data from a **Total Lightning Processor**. The data can be visualized as a product layer, which can be shown on top of a weather radar product layer. A separate license is required for visualizing lightning data from the Vaisala precision lightning sensor network.

- *On-demand lightning TimeSpan product generation*  
The new **TimeSpan** lightning product enables the user to visualize the evolution of recent lightning events. The TimeSpan product shows lightning events as color-coded areas that change over time. The timeline histogram shows information about strikes up to 7 days in the past at rates as high as 100,000 events per day. When viewing in real time, the product shows new lightning events as they occur.
- *Lightning network health visualization*  
IRIS Focus enables the user to visualize the performance of the lightning sensor network. The **Network Health** product uses a color-coded grid representation of the performance estimate generated by the Total Lightning Processor (TLP). This is an advanced feature that works with a separate license.
- *Lightning cursor tool*  
IRIS Focus enables the user to view details of the lightning data and the network health information with the cursor tool. The tool includes the location of the strike, with accuracy represented by the error ellipse.

## Updates

- *Weather pane layers*  
The ordering of the weather layers has been improved. Now the layer number 1 is on the top. When the user adds a new layer, the layer is added on top, and the existing layers move down in the list.
- *New user roles*  
The **Focus** user role has been replaced with two separate user roles: **Focus Weather Radar User** for users who want to view weather radar data, and **Focus Lightning User** for users who want to view lightning data. The current **Focus** users will be automatically upgraded to **Focus Weather Radar User** roles.
- *Nowcasting on a separate server*  
IRIS Focus Nowcasting feature can now be run in a separate server for improving performance. For detailed instructions, see chapter *Installing nowcasting as a separate service* in *IRIS Focus Administrator Guide*.
- *Licensing: License required for adding more radars*  
The new licenses are issued with a defined number of radar sites. If the network contains more radars than the number of the radar sites in the license, the user can define which radars are shown in the application by editing the [LICENSING] section in the *vsoweb-override.ini* file. If the customer has an active service contract, the new license will be updated according to the existing number of sites connected to the application.
- *Licensing: License required for visualizing external WMS layers*  
A license is required for visualizing external WMS layers in the application. If the customer has an active service contract, the new license will be updated to include this license.

- *Installation:*

The `cors-origin-whitelist (-cow)` switch has been added to the installation script for determining the value of the “`Access-Control-Allow-Origin`” header. It must have the same value as the root application URL. The value defaults to the installation machine name.

Installation command :

```
/srv/Vaisala-IRIS-Focus-v6.x.x/rsw-installer --offline --gisdb dump
vaisala-iris-maps-v2 --terrain-dir vaisala-iris-terrain-v2 -radar -s
<hostname or IP of IRIS Analysis socket server> -cow <root application URL>
```

## Fixes

- 7695: Smoothing knob misbehavior when changing datatypes
- 7294, 6920: User-defined color scales revert to default without user interaction
- 7727, 7980: Tools and alerts shall not need to have an on-demand product as a driving product
- 7702: LOG,CSR,PMI, and XCORV data types shall display properly
- 7753, 7159: Alerts using IRIS Analysis products (VIL, SHEAR, RAINN) shall be triggered
- 7852: Cross Section Tool image blank
- 7899: When switching tasks quickly, an error was prompted
- 8041: Alert icons shall show regardless of the layer order

## 2.3 Known issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- IRIS Focus WMS feature currently works with WMS version 1.1.1.
- Currently, the alerting functionality is limited to single radar sites only. Alerts are not generated for composite sites.
- 5408: Tile view does not work in kiosk mode.
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps. The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6953: Timeline needs to be clicked twice to get a product after panning.
- 6974: Two WMS layers with same layer name causes the application not to respond.
- 7472: When using the Hayford-Gauss projection, there are inconsistencies in map behavior at the edge of the map.

- "Anonymous" entries in the user table occur if someone attempts to access IRIS Focus using a bad URL. If you see a lot of these in your table with external IP addresses, it may indicate that the server is under attack.

## 2.4 Upgrading IRIS Focus 5.0 or later to IRIS Focus 6.0

The following instructions assume that you are upgrading from IRIS Focus 5.0 or a later version to IRIS Focus 6.0.



You can upgrade to IRIS Focus 6.0 from IRIS Focus 5.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through previous versions to IRIS Focus 5.0 before you can upgrade to IRIS Focus 6.0.

### 2.4.1 License

This upgrade requires a new license. The upgrade instructions include a step for identifying the Lock ID that you need for getting the new license.

If you have a contract agreement with Vaisala, you should receive your upgrade license via email. If you have not received the license, please contact Vaisala technical support at [helpdesk@vaisala.com](mailto:helpdesk@vaisala.com). In other cases, please contact your Vaisala Sales representative to get a new license.



**CAUTION!** It is possible to upgrade your system without a valid license with the command `./rsw-upgrade --online --skip-license`, but it is not recommended. Upgrading without a valid license will cause your system to stop or run in a degraded state until you receive and install a valid license file.

### 2.4.2 Running the upgrade



To view installation command line options, run: `./rsw-upgrade -h`



If you have your license key on a USB drive, make sure it is inserted in the server before starting the upgrade procedure.

In the following instructions, `x.x` means the Iris Focus version and patch number.

1. Log in as **root**.

2. Backup the system configuration.  
For instructions, see *IRIS Focus Administrator Guide*.
3. Insert the upgrade USB stick.
4. Copy the file `Vaisala_IRIS_installer-6.x.x.tar` from the USB stick to the server's hard disk drive, for example, to the `/root` directory.
5. Change to the `/root` directory and extract the `.tar` file:

```
tar -xvf Vaisala_IRIS_installer-6.x.x.tar
```

where `x.x` is the Iris Focus version and patch number.

6. Change to the directory created in the earlier step:

```
cd Vaisala-IRIS-Focus-v6.x.x
```

7. If you already have a new license, proceed to step [step 10](#). If you do not have a new license file yet, type the following command to identify your system's Lock ID:

```
./rsw-license-info
```

The output shows your system's new Lock ID, as well as information indicating that the current license file is invalid. Example:

```
Lock ID: *1KTW99ERX5MBRL2
Error: Locking criteria should be 0x18 or 0x80. It is: 0x4.
IniFile: license/license.ini
LicFile: /etc/vaisala/radarsw/configuration/license.txt
Version: n/a
Valid: false
Active: false
Starts: n/a
Ends: n/a
```

8. Contact Vaisala Technical support or your Vaisala Representative to get the license file. You will need to provide the Lock ID.

9. When you have received the new license file and saved it on your server, verify that it is valid with the command:

```
./rsw-license-info --license /mnt/usb/license-6.x.x.txt
```

where you replace `/mnt/usb/license-6.x.x.txt` with the location of your license file.

If the license file is valid, both the **Valid** and **Active** fields will report **true**. Example:

```
Lock ID: *1KTW99ERX5MBRL2
IniFile: license/license.ini
LicFile: /mnt/usb/license-5.3.txt
Version: 6.0
Valid: true
Active: true
Starts: 2010-01-01T00:00:00Z
Ends: 2021-12-31T00:00:00Z
Feature: IRIS_Focus_Lightning (seats: 10)
Feature: IRIS_Focus_Light_LGT (seats: 50)
Feature: IRIS_Focus_Light_WR (seats: 50)
Feature: IRIS_WMS (seats: 10)
Feature: IRIS_Focus_Version (seats: 10)
Feature: IRIS_NetworkHealth_LGT (seats: 50)
Feature: IRIS_Focus_Weather_Radar (seats: 10)
Feature: IRIS_Nowcast (seats: 10)
```

10. Run the upgrade script:

- **Online upgrade:**

```
./rsw-upgrade --online --license /mnt/usb/license-6.x.x.txt
```

- **Offline upgrade:**

```
./rsw-upgrade --offline --license /mnt/usb/license-6.x.x.txt
```

11. Verify the upgrade by running: **rpm -qa | grep vaisala**  
Check that the `rpm` name is the correct version and patch number.



If you have a Total Lightning Processor (TLP) system that you will be connecting to your IRIS Focus server, see connection instructions in *M212545EN IRIS Focus Lightning Administrator Guide*.

After connecting the TLP system, add the **focus-lightning** role to each existing user account that you want to have access to the lightning products. See section [Updating user roles \(page 10\)](#).

### 2.4.3 Updating user roles

After the upgrade, depending on your system, you may need to update the user roles for the users.

If there are a lot of users in the system, you can easily update all the existing user accounts with the following instructions:

- If you have had only weather radars in the system, and you are now adding a lightning network: Update all the existing user accounts that currently have the **focus-radar** role to also have the **focus-lightning** role. Use this command (as **root**):

```
rsw-db-tool users-to-all-focus-roles
```

- If you only have a lightning network in the system: Give all the users the **focus-lightning** role. Use this command (as **root**):

```
rsw-db-tool users-to-ltg-role
```

- If you only have weather radars in the system: You should not need to manually update roles. All **focus** users are automatically updated to **focus-radar** users by the upgrade script. If this does not happen, run this command:

```
rsw-db-tool users-to-radar-role
```

## 2.5 Installation command options

Table 4 Installation command options

Option	Description
--admin-password	Assign a non-default admin password
--admin-user	Assign a non-default admin user
-c --config-dir	Configuration directory

Option	Description
--deactivate-admin	Deactivate the admin account after running this script. Not needed for standard installations.
-d --dry-run	List the steps that will be run (without running them)
-g --geoserver-config-url	GeoServer configuration endpoint (default: <a href="http://localhost:34180/geoserver">http://localhost:34180/geoserver</a> )
-gis-db-dump	Location of map files
-h	Show help information
--lightning	Allow configuration for lightning provider
--no-prompt	Fails (exits) on error without user confirmation
--nowcast-only	Only install Nowcast on this host
--offline	Disable online CentOS base repository and require a local CentOS base repository
--online	Allow online CentOS base repository
--pg-data-dir	Use an alternative Postgres data directory location
--radar	Allow configuration for radar provider
-s	Socket server host
--skip-geoserver-installation	Do not install map server
--skip-geoserver-site-configuration	
--skip-os-version-check	Force the installation on a CentOS version other than directly supported
--skip-terrain	Do not install terrain detail to the map server
--terrain-dir	Location of terrain files
--tlp TLP_ADDRESS	Address of the Total Lightning Processor
--wms -w	Basemap WMS address (default: /wms)

Table 5 Post-installation command options

Option <sup>1)</sup>	Description
<b>radar.enabled = true</b>	Allow configuration for radar provider
<b>lightning.enabled = true</b>	Allow configuration for lightning provider

1) These can be changed in *vsoweb-override.ini* config file

## 3. IRIS Focus 5.3 release notes

### 3.1 Release notices

Vaisala is pleased to announce the release of IRIS Focus 5.3.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

#### Upgrade to IRIS Focus 5.3

You can upgrade to IRIS Focus 5.3 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.3.

When upgrading to 5.3, the maps will stay installed.



**CAUTION!** When you upgrade from IRIS Focus 4.0 to 5.3, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade.



When you upgrade from IRIS Focus 5.0/5.1/5.2 to 5.3, the data in Data Manager is not deleted.



Vaisala recommends you back-up your system configuration before upgrading. For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.

Table 6 System requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.3 has been tested with CentOS 7.4 and 7.6. IRIS Focus is also expected to work with other versions of CentOS 7.x.	IRIS Focus 5.3 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 3.2 Updates and fixes

### New features

- *Selection of map projection*  
IRIS Focus now enables the poweruser to set the map projection in which all the users will see the data displayed. Currently, the following projections are supported: azimuthal equidistant, Web Mercator, and Hayford-Gauss.



IRIS Focus 5.3 includes the addition of the EPSG:27493 map projection. This map projection is optional and can be configured by the poweruser. Because of its location and limited range, we only recommend using this projection if you have a very specific need.

### Updates

- Security: Adjustments were made to the HTTP headers produced by the web server to increase security and remove ambiguity.
- License logging: Logging message improvement for versioning.

### Fixes

- 7403: Cross-Section and Max panels faulty color ray when there was a NOT\_SCANNED value in the data
- 7409: When upgrading IRIS Focus to the 5.2 release over a 5.1.2 or 5.1.3 patch, the upgrade fails on the version check, as it does not properly check the version number retrieved from the patch file.

## 3.3 Known issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- 5408: Tile view does not work in kiosk mode.
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps. The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6953: Timeline needs to be clicked twice to get a product after panning.
- 6974: Two WMS layers with same layer name causes the application not to respond.
- 7472: When using the Hayford-Gauss projection, there are inconsistencies in map behavior at the edge of the map.

## 3.4 Upgrading IRIS Focus 4.0 or later to IRIS Focus 5.3

The following instructions assume that you are upgrading from IRIS Focus 4.0 or a later version to IRIS Focus 5.3.



You can upgrade to IRIS Focus 5.3 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.3.



**CAUTION!** When you upgrade from IRIS Focus 4.0 to 5.3, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade.



When you upgrade to IRIS Focus 5.3 from version that is later than 4.0, the data in Data Manager is not deleted.



Vaisala recommends you back-up your system configuration before upgrading. For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.



**CAUTION!** The addition of the EPSG:27493 map projection in IRIS Focus 5.3 includes several modifications to the configuration files and the tile caching for the "vaisala" map layers in the GeoServer running on IRIS Focus. For most installations, this enhancement is fully automatic when you run the **rsw-upgrade** script. However, if you have configured IRIS Focus 5.3 to use an EXTERNAL GeoServer for its map tiles, AND you want to use the EPSG:27493 map projection, you need to edit the configuration files and tile caching on your custom GeoServer, so that it can render tiles in the EPSG:27493 projection. If you do not edit these configuration files, the map will not render properly or at all when IRIS Focus is configured by the poweruser to use the EPSG:27493 map projection.

After upgrading from IRIS Focus 4.0 to 5.3, you need to re-create your areas of interest.

### 3.4.1 License

This upgrade requires a new license. The upgrade instructions include a step for identifying the Lock ID that you need for getting the new license.

If you have a contract agreement with Vaisala, you should receive your upgrade license via email. If you have not received the license, please contact Vaisala technical support at [helpdesk@vaisala.com](mailto:helpdesk@vaisala.com). In other cases, please contact your Vaisala Sales representative to get a new license.



**CAUTION!** It is possible to upgrade your system without a valid license with the command `./rsw-upgrade --online --skip-license`, but it is not recommended. Upgrading without a valid license will cause your system to stop or run in a degraded state until you receive and install a valid license file.

### 3.4.2 Running the upgrade



To view installation command line options, run: `./rsw-upgrade -h`



If you have your license key on a USB drive, make sure it is inserted in the server before starting the upgrade procedure.

In the following instructions, `x.x` means the Iris Focus version and patch number.

- ▶ 1. Log in as **root**.
2. Backup the system configuration.  
For instructions, see *IRIS Focus Administrator Guide*.
3. Insert the upgrade USB stick.
4. Copy the file `Vaisala_IRIS_installer-6.x.x.tar` from the USB stick to the server's hard disk drive, for example, to the `/root` directory.
5. Change to the `/root` directory and extract the `.tar` file:

```
tar -xvf Vaisala_IRIS_installer-6.x.x.tar
```

where `x.x` is the Iris Focus version and patch number.

6. Change to the directory created in the earlier step:

```
cd Vaisala-IRIS-Focus-v6.x.x
```

7. If you already have a new license, proceed to step [step 10](#). If you do not have a new license file yet, type the following command to identify your system's Lock ID:

```
./rsw-license-info
```

The output shows your system's new Lock ID, as well as information indicating that the current license file is invalid. Example:

```
Lock ID: *1KTW99ERX5MBRL2
Error: Locking criteria should be 0x18 or 0x80. It is: 0x4.
IniFile: license/license.ini
LicFile: /etc/vaisala/radarsw/configuration/license.txt
Version: n/a
Valid: false
Active: false
Starts: n/a
Ends: n/a
```

8. Contact Vaisala Technical support or your Vaisala Representative to get the license file. You will need to provide the Lock ID.

9. When you have received the new license file and saved it on your server, verify that it is valid with the command:

```
./rsw-license-info --license /mnt/usb/license-6.x.x.txt
```

where you replace `/mnt/usb/license-6.x.x.txt` with the location of your license file.

If the license file is valid, both the **Valid** and **Active** fields will report **true**. Example:

```
Lock ID: *1KTW99ERX5MBRL2
IniFile: license/license.ini
LicFile: /mnt/usb/license-5.3.txt
Version: 6.0
Valid: true
Active: true
Starts: 2010-01-01T00:00:00Z
Ends: 2021-12-31T00:00:00Z
Feature: IRIS_Focus_Lightning (seats: 10)
Feature: IRIS_Focus_Light_LGT (seats: 50)
Feature: IRIS_Focus_Light_WR (seats: 50)
Feature: IRIS_WMS (seats: 10)
Feature: IRIS_Focus_Version (seats: 10)
Feature: IRIS_NetworkHealth_LGT (seats: 50)
Feature: IRIS_Focus_Weather_Radar (seats: 10)
Feature: IRIS_Nowcast (seats: 10)
```

10. Run the upgrade script:

- **Online upgrade:**

```
./rsw-upgrade --online --license /mnt/usb/license-6.x.x.txt
```

- **Offline upgrade:**

```
./rsw-upgrade --offline --license /mnt/usb/license-6.x.x.txt
```

11. Verify the upgrade by running: **rpm -qa | grep vaisala**  
Check that the `rpm` name is the correct version and patch number.



If you have a Total Lightning Processor (TLP) system that you will be connecting to your IRIS Focus server, see connection instructions in *M212545EN IRIS Focus Lightning Administrator Guide*.

After connecting the TLP system, add the **focus-lightning** role to each existing user account that you want to have access to the lightning products. See section [Updating user roles \(page 10\)](#).

# 4. IRIS Focus 5.2 release notes

## 4.1 Release notices

Vaisala is pleased to announce the release of IRIS Focus 5.2.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

### Upgrade to IRIS Focus 5.2

You can upgrade to IRIS Focus 5.2 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.2. After upgrading from IRIS Focus 4.0 to 5.2, you need to re-create your areas of interest.



Upgrading to IRIS Focus 5.2 requires a new license. If you have a contract agreement with Vaisala, you will receive your upgrade license via email. If you have not received the license, please contact Vaisala technical support at [helpdesk@vaisala.com](mailto:helpdesk@vaisala.com). In other cases, please contact your Vaisala Sales representative to get a new license.



**CAUTION!** When you upgrade from IRIS Focus 4.0 to 5.2, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade. Vaisala recommends you back-up your system configuration before upgrading. For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.



When you upgrade from IRIS Focus 5.0/5.1 to 5.2, the data in Data Manager is not deleted.

Table 7 System requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.2 has been tested with CentOS 7.4 and 7.6. IRIS Focus is also expected to work with other versions of CentOS 7.x.	IRIS Focus 5.2 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 4.2 Updates and fixes

### New features

- *Housekeeping service for alerts*  
IRIS Focus now has the capability to clean the alerts database and to trigger a technical alert when the alerts database load is approaching the configured limit. The user can select the limit that triggers the alert. The default is 90% of maximum database usage. The database size limit is set automatically depending on the partition/disk size reported by the operating system during the install, but can be changed by the user. The user can also configure the clean-up target. The clean-up target tells how many of the latest alerts will be kept in the database. By default, this feature is ON. The user can change the settings in the *vsoweb-override.ini* file.  
If the user wants to save the old alerts, a manual backup of the database is recommended. Alternatively, more disk space can be added to the server, and a new minimum number of entries set.
- *Partial hybrid scans*  
The user can now select whether or not to visualize partial hybrid scans. The user can decide whether the displayed product at a specific time will contain all the hybrid scans or not. By default, the user will see partial hybrid volume scans. To visualize only complete volume scans, the user needs to set the `use.partial.hybrid.times` parameter to **False** in the **[HYBRID\_PRODUCT\_TIMES]** section of the *vsoweb-override.ini* file.

### Updates

- IRIS Focus licensing: The major and minor versions of the software will need a new license
- Timeline: The button for showing the present time is now called **Now**.

- User roles:
  - The admin role no longer includes the ability to manage product configuration.
  - The poweruser role now includes the ability to manage product configuration through the **Product Configuration** panels.




Figure 1 Product configuration

If you have a user with the admin role, and you want this user to be able to manage product configuration, edit the user account information to give the user both the admin role and the poweruser role.

## Fixes

- 7398: Events and alerts not filtered for user.
- 7397: Timeline scrolling issue if mouse pointer drifts off the timeline before the button is released.
- 7396: Timeline shifts after some time when right knob is moved to the left.
- 7349: Ruler tool shift-click second point broken.
- 7146: Correct handling of hybrid tasks by IRIS Focus Data Manager.
- 6950: Timeline moves when animation is set in the past.
- 6824: Timeline resizes automatically.
- 6680: A delay has been added for stopping or restarting the `vaisala-radar-sw-webapp` service. This makes the restart operation more consistent. However, if the `monit` service is running when the restart is issued, it is possible that `monit` attempts to start the `vaisala-radar-sw-webapp` during the restart. This can trigger an error message. If you receive an error message about the restart being canceled, you can use the following status command to verify that the service did actually start:

```
systemctl status vaisala-radar-sw-webapp
```

- 7220: Improvements for Data Manager logging.

## 4.3 Known issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- 5408: Tile view does not work in kiosk mode.
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps.  
The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6864: Nowcast: Timeline hatched area doesn't sync up with advected products.
- 6953: Timeline needs to be clicked twice to get a product after panning.
- 6974: Two WMS layers with same layer name causes the application not to respond.
- 7409: When upgrading IRIS Focus to the 5.2 release over a 5.1.2 or 5.1.3 patch, the upgrade fails on the version check as it doesn't properly check the version number retrieved from the patch file. Add the `--skip-version-check` flag to the upgrade command to avoid the issue.

## 4.4 Upgrading IRIS Focus 4.0 or later to IRIS Focus 5.3

The following instructions assume that you are upgrading from IRIS Focus 4.0 or a later version to IRIS Focus 5.3.



You can upgrade to IRIS Focus 5.3 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.3.



**CAUTION!** When you upgrade from IRIS Focus 4.0 to 5.3, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade.



When you upgrade to IRIS Focus 5.3 from version that is later than 4.0, the data in Data Manager is not deleted.



Vaisala recommends you back-up your system configuration before upgrading. For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.



**CAUTION!** The addition of the EPSG:27493 map projection in IRIS Focus 5.3 includes several modifications to the configuration files and the tile caching for the "vaisala" map layers in the GeoServer running on IRIS Focus. For most installations, this enhancement is fully automatic when you run the **rsw-upgrade** script. However, if you have configured IRIS Focus 5.3 to use an EXTERNAL GeoServer for its map tiles, AND you want to use the EPSG:27493 map projection, you need to edit the configuration files and tile caching on your custom GeoServer, so that it can render tiles in the EPSG:27493 projection. If you do not edit these configuration files, the map will not render properly or at all when IRIS Focus is configured by the poweruser to use the EPSG:27493 map projection.

After upgrading from IRIS Focus 4.0 to 5.3, you need to re-create your areas of interest.

#### 4.4.1 License

This upgrade requires a new license. The upgrade instructions include a step for identifying the Lock ID that you need for getting the new license.

If you have a contract agreement with Vaisala, you should receive your upgrade license via email. If you have not received the license, please contact Vaisala technical support at [helpdesk@vaisala.com](mailto:helpdesk@vaisala.com). In other cases, please contact your Vaisala Sales representative to get a new license.



**CAUTION!** It is possible to upgrade your system without a valid license with the command `./rsw-upgrade --online --skip-license`, but it is not recommended. Upgrading without a valid license will cause your system to stop or run in a degraded state until you receive and install a valid license file.

#### 4.4.2 Running the upgrade



To view installation command line options, run: `./rsw-upgrade -h`



If you have your license key on a USB drive, make sure it is inserted in the server before starting the upgrade procedure.

In the following instructions, `x.x` means the Iris Focus version and patch number.

1. Log in as **root**.
2. Backup the system configuration.  
For instructions, see *IRIS Focus Administrator Guide*.
3. Insert the upgrade USB stick.
4. Copy the file `Vaisala_IRIS_installer-6.x.x.tar` from the USB stick to the server's hard disk drive, for example, to the `/root` directory.
5. Change to the `/root` directory and extract the `.tar` file:

```
tar -xvf Vaisala_IRIS_installer-6.x.x.tar
```

where `x.x` is the Iris Focus version and patch number.

6. Change to the directory created in the earlier step:

```
cd Vaisala-IRIS-Focus-v6.x.x
```

7. If you already have a new license, proceed to [step 10](#). If you do not have a new license file yet, type the following command to identify your system's Lock ID:

```
./rsw-license-info
```

The output shows your system's new Lock ID, as well as information indicating that the current license file is invalid. Example:

```
Lock ID: *1KTW99ERX5MBRL2
Error: Locking criteria should be 0x18 or 0x80. It is: 0x4.
IniFile: license/license.ini
LicFile: /etc/vaisala/radarsw/configuration/license.txt
Version: n/a
Valid: false
Active: false
Starts: n/a
Ends: n/a
```

8. Contact Vaisala Technical support or your Vaisala Representative to get the license file. You will need to provide the Lock ID.

9. When you have received the new license file and saved it on your server, verify that it is valid with the command:

```
./rsw-license-info --license /mnt/usb/license-6.x.x.txt
```

where you replace `/mnt/usb/license-6.x.x.txt` with the location of your license file.

If the license file is valid, both the **Valid** and **Active** fields will report **true**. Example:

```
Lock ID: *1KTW99ERX5MBRL2
IniFile: license/license.ini
LicFile: /mnt/usb/license-5.3.txt
Version: 6.0
Valid: true
Active: true
Starts: 2010-01-01T00:00:00Z
Ends: 2021-12-31T00:00:00Z
Feature: IRIS_Focus_Lightning (seats: 10)
Feature: IRIS_Focus_Light_LGT (seats: 50)
Feature: IRIS_Focus_Light_WR (seats: 50)
Feature: IRIS_WMS (seats: 10)
Feature: IRIS_Focus_Version (seats: 10)
Feature: IRIS_NetworkHealth_LGT (seats: 50)
Feature: IRIS_Focus_Weather_Radar (seats: 10)
Feature: IRIS_Nowcast (seats: 10)
```

10. Run the upgrade script:

- **Online upgrade:**

```
./rsw-upgrade --online --license /mnt/usb/license-6.x.x.txt
```

- **Offline upgrade:**

```
./rsw-upgrade --offline --license /mnt/usb/license-6.x.x.txt
```

11. Verify the upgrade by running: **rpm -qa | grep vaisala**  
Check that the `rpm` name is the correct version and patch number.



If you have a Total Lightning Processor (TLP) system that you will be connecting to your IRIS Focus server, see connection instructions in *M212545EN IRIS Focus Lightning Administrator Guide*.

After connecting the TLP system, add the **focus-lightning** role to each existing user account that you want to have access to the lightning products. See section [Updating user roles \(page 10\)](#).

# 5. IRIS Focus 5.1.1 Release Notes

## 5.1 Release Notices

These notes are for the IRIS Focus patch release, 5.1.1. This is a patch for IRIS Focus 5.1. For more information on IRIS Focus 5.1, see the IRIS Focus 5.1 Release Notes, IRIS Focus Administrator Guide, and IRIS Focus User Guide.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

### Upgrade to IRIS Focus 5.1.1

You can upgrade to IRIS Focus 5.1.1 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.1.1.



**CAUTION!** When you upgrade from IRIS Focus 4.0 (or 4.0.1) to 5.1.1, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade. Vaisala recommends you back-up your system configuration before upgrading.

For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.

When you upgrade from IRIS Focus 5.0/5.1 to 5.1.1, the data in Data Manager is not deleted.

Table 8 System Requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.1.1 has been tested with CentOS 7.4 and 7.6. IRIS Focus is also expected to work with other versions of CentOS 7.x.	IRIS Focus 5.1.1 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 5.2 Fixes

### Fixes

- 6957 and 6964: The functionality of events and alerts on hybrid tasks has been improved
- 6965: haproxy logs grow without cleanup
- 6960: Product request latency performance improvement

- 6961: FireEventServiceGwt calls should not be made when alert layer is off and protected area layer is on

## 5.3 Known Issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- 5408: Tile view does not work in kiosk mode.
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps.  
The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6680: When the restart service of the web application is used, the application sometimes does not have time to change the settings properly. You must add a delay by running the following commands :

```
systemctl stop vaisala-radarsw-webapp
```

Wait approximately 15 seconds and then run:

```
systemctl start vaisala-radarsw-webapp
```

- For external WMS layers, the cursor tool functionality does not work on Internet Explorer 11 due to Cross-Origin Resource Sharing (CORS) limitations in that browser.
- 6944: With Internet Explorer, it is not possible to save Areas of Interest with height products.

# 6. IRIS Focus 5.1. Release Notes

## 6.1 Release Notices

Vaisala is pleased to announce the release of IRIS Focus 5.1.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

### Upgrade to IRIS Focus 5.1

You can upgrade to IRIS Focus 5.1 from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.1.



**CAUTION!** When you upgrade from IRIS Focus 4.0 (or 4.0.1) to 5.1, the data in Data Manager is deleted. The MVF and composite definitions are also no longer available after the upgrade. Vaisala recommends you back-up your system configuration before upgrading.

For information on adding the historical data to your system after the upgrade, see *IRIS Focus Administrator Guide*.

When you upgrade from IRIS Focus 5.0 to 5.1, the data in Data Manager is not deleted.

Table 9 System Requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.1 has been tested with CentOS 7.4 and 7.6. IRIS Focus is also expected to work with other versions of CentOS 7.x.	IRIS Focus 5.1 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 6.2 Updates and Fixes

### New Features

- *External WMS (Web Map Services) layer support for data visualization*  
You can now visualize data from external sources, such as satellite images and data from external radar networks, together with weather radar products.
- *Easy identification of the alert-triggering radar*  
The alert pane now includes the name of the radar that generated the alert-triggering data.

## Updates

- The animation speed is now faster than in earlier releases. The highest possible speed is 25 frames/second. However, the speed may vary depending on the circumstances, such as connection speed and data shown on the screen.
- *IRIS Focus User Guide* now includes a detailed description of events and alerts.

## Fixes

- 6802: IRIS Focus shall be able to handle faulty socket server products.
- 6803: Focus light user unknown errors shall be handled.
- 6804: Side panel Max products display delayed when logged as IRIS Focus\_light user.
- 6805: Range rings of the previously selected site are shown in the composite view.
- 6807: The Snapshot feature only works with recent data, not when displaying historical data.
- 6476: Criteria: threshold does not accept a negative number.
- 6666: The events and alerts feature provides information in metric units throughout the configuration and display process.
- 6825: Animation speed doesn't fit the animation setting and it is too slow for forecaster use.
- 6876: Multiple alerts pop up even if the area is small.
- 6951: No product updates when timeline not moved.

## 6.3 Known Issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps.  
The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 5408: Tile view does not work in kiosk mode.

- 6680: When the restart service of the web application is used, the application sometimes does not have time to change the settings properly. You must add a delay by running the following commands :

```
systemctl stop vaisala-radarsw-webapp
```

Wait approximately 15 seconds and then run:

```
systemctl start vaisala-radarsw-webapp
```

- For external WMS layers, the cursor tool functionality does not work on Internet Explorer 11 due to Cross-Origin Resource Sharing (CORS) limitations in that browser.
- 6944: With Internet Explorer, it is not possible to save Areas of Interest with height products.

## 6.4 Upgrading IRIS Focus 4.0 or 5.0 to IRIS Focus 5.1

The following instructions assume that you are upgrading from IRIS Focus 4.0 or a later version to IRIS Focus 5.1.



You can upgrade to IRIS Focus 5.1. from IRIS Focus 4.0 or a later version. If you have an earlier version of IRIS Focus, you must upgrade through each previous version to IRIS Focus 4.0 before you can upgrade to IRIS Focus 5.1.



**CAUTION!** This procedure deletes the contents of the data manager database. Make sure you back-up the database before you begin. The database will repopulate when you begin to run data after the upgrade.

- ▶ 1. Log in as **root**.
2. Backup the system configuration.  
See [Making a manual back-up \(page 40\)](#).
3. Insert the upgrade USB stick.
4. Copy the file *Vaisala\_IRIS\_installer-5.1.tar* from the USB stick to the server's hard disk drive, for example to the */root* directory.

5. Change to the */root* directory and extract the *.tar* file:

```
#tar -xvf Vaisala_IRIS_installer-5.1.tar
```

6. Change to the directory created in the earlier step:

```
Vaisala-IRIS-Focus-v5.1-RC1--69
```

7. Run the upgrade script.

**Online upgrade:**

```
./rsw-upgrade --online
```

**Offline upgrade:**

```
./rsw-upgrade --offline
```



To view installation command line options, run: **./rsw-upgrade -h**

8. Verify the upgrade by running: **rpm -qa | grep vaisala**  
Check that the **rpm** name is version 5.1.

# 7. IRIS Focus 5.0.1 Release Notes

## 7.1 Release Notices

These notes are for the IRIS Focus patch release, 5.0.1. This is a patch for IRIS Focus 5.0. For more information on IRIS Focus 5.0, see the IRIS Focus 5.0 Release Notes, *IRIS Focus Administrator Guide*, and *IRIS Focus User Guide*.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

### Upgrade to IRIS Focus 5.0.1

Table 10 System Requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.0.1 has been tested with CentOS 7.4, and is assumed to work with newer versions of the software.	IRIS Focus 5.0.1 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 7.2 Fixes

- 6216: If the IRIS Analysis machine that works as socket server is set to local time, the IRIS Analysis products are shown in the wrong time in IRIS Focus. Vaisala recommends that you setup the whole network in UTC time.  
For this fix to work properly, you must install a patch for IRIS Analysis software that is installed on the machine that serves the product to IRIS Focus. For the correct patch, see the following table.

Table 11 IRIS Analysis versions and required sw patches

IRIS Analysis version	Required patch version
IRIS 8.13.6	IRIS/RDA Patch 6
IRIS 8.13.7	IRIS/RDA Patch 9
IRIS 9.0.0	IRIS/RDA Patch 3

- 6382: Data manager is not able to read the IRIS RAW products generated from *odim\_HDF5* files that do not contain all the required parameters.

## 7.3 Known Issues

- 5408: Tile view does not work in kiosk mode.
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps.  
The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6666: The events and alerts feature provides information in metric units throughout the configuration and display process.
- 6680: When the restart service of the web application is used, the application sometimes does not have time to change the settings properly. You must add a delay by running the following commands :

```
systemctl stop vaisala-radarsw-webapp
```

Wait approximately 15 seconds and then run:

```
systemctl start vaisala-radarsw-webapp
```

## 7.4 Upgrading IRIS Focus 5.0 to IRIS Focus 5.0.1

The following instructions assume you are upgrading from IRIS Focus 5.0 to IRIS Focus 5.0.1.



If you have previous versions of IRIS Focus, you must upgrade through each previous version before you can upgrade to IRIS Focus 5.0.1.



**CAUTION!** This procedure deletes the contents of the data manager database. Make sure you back-up the database before you begin. The database will repopulate when you begin to run data after the upgrade.

1. Log in as **root**.
2. Backup the system configuration.  
See [Making a manual back-up \(page 40\)](#).
3. Insert the upgrade USB stick.

4. Copy the file *Vaisala\_IRIS\_installer-5.0.1.tar* from the USB stick to the server's hard disk drive, for example to the */root* directory.
5. Change to the */root* directory and extract the *.tar* file:

```
#tar -xvf Vaisala_IRIS_installer-5.0.1.tar
```

6. Change to the directory created in :

```
Vaisala-IRIS-Focus-v5.0.1-RC1--69
```

7. Run the upgrade script.

**Online upgrade:**

```
./rsw-upgrade --online
```

**Offline upgrade:**

```
./rsw-upgrade --offline
```



To view installation command line options, run: **./rsw-upgrade -h**

8. Verify the upgrade by running: **rpm -qa | grep vaisala**  
Check that the **rpm** name is version 5.0.1.

# 8. IRIS Focus 5.0 Release Notes

## 8.1 Release Notices

Vaisala is pleased to announce the release of IRIS Focus 5.0.

IRIS Focus supports current Microsoft Edge®, Mozilla Firefox®, and Google Chrome™ browsers.

### Upgrade to IRIS Focus 5.0

You can only upgrade IRIS Focus gradually, that is, one version at a time. You can only perform upgrade to IRIS Focus 5.0 from IRIS Focus 4.0. For upgrading instructions, see *IRIS Focus Administrator Guide*.



**CAUTION!** Vaisala recommends you back-up your system configuration before upgrading. Information in data manager is not backed-up during the upgrade. This means that after the upgrade, data showed in the previous version of IRIS Focus is no longer available. After some time, new data will be provided from the radars in your network through data manager. For information on adding historical data to your system, see *IRIS Focus Administrator Guide*.

Table 12 System Requirements

CentOS	IRIS Analysis/IRIS Radar
IRIS Focus 5.0 has been tested with CentOS 7.4, and is assumed to work with newer versions of the software.	IRIS Focus 5.0 requires IRIS Analysis/Radar 8.13.6 or later on the same network. Note that IRIS Analysis must not be visible to the public Internet.

## 8.2 Updates and Fixes

### New Features

- *Weather events and alerts*  
You can now define the weather event criteria for identifying significant weather events and alerts directly in IRIS Focus.  
To receive alerts about significant weather, you can assign one or more sets of event criteria to an area of interest.

- *Areas of interest*  
IRIS Focus 5.0 has further optimized our tools for assigning weather criteria to areas of interest.  
You can create circular and polygon areas of interest.  
After you assign configurable weather event criteria to an area, you will automatically receive alerts when weather events cross into that area. You can manage which areas are active one by one.
- *Pin places of interest*  
You can add pins to the map to indicate points of interest. The pins provide useful reference points and labels.
- *Ruler Tool*  
Select **Tools > Ruler Tool** to measure the distance between two points on the map with two simple clicks of the mouse.
- *Data flow monitoring*  
IRIS Focus administrator can setup data flow alerts for monitoring the data to IRIS Focus. IRIS system provides a way of detecting the frequency of the product arrival.

## Updates

- Introduction of the use of the *poweruser* role.  
The specific functions for a user with this role are: creating global areas of interest, and creating event criteria, such as thunderstorm, shear, or lightning.
- For security reasons, the application software now only allows a single log in for each user. A single user can use several sessions in the same browser.  
However, if another user uses the same login from a different IP, the logged user will be logged out.
- The **Cross Section**, **Tracking Tool**, and **Ruler Tool** are now grouped behind the **Tools** button.

## Fixes

- Data Manager fixes:
  - 5535/6218 Sector scan and missing rays: Radar product generation does not support missing rays and sector scan are shown in the wrong azimuth angle.
  - 6227/6262/6263/6296/6552 Data manager housekeeping service:
    - Properly deleting unused volume\_conf\_to\_source records
    - Paging to Data Manager's housekeeping service so that 1000 volumes are deleted at a time to avoid spike in heap space
    - Data Manager housekeeping speed improvement
    - Handle exception when data is deleted from the database accidentally
  - 6291/6293 RHI Hybrid RAW file management: RHI RAW data and Hybrid naming is causing errors in the data manager
  - 6290: There shall not exist a ray count dependency in data manager
- Image export:
  - 6143 Unexpected error caused by no available data in the present time
- Alerts
  - 5418 Unique name for Areas of Interest
  - 6580 Just events from the last 48h show on the UI

## 8.3 Known Issues



For troubleshooting information, see *IRIS Focus Administrator Guide*.

- 5408: Tile view does not work in kiosk mode
- 5660: The user interface uses UTC as the default timezone. If the user changes the timezone in the **Admin** panel, the new timezone is not displayed in the web user interface.
- 5704: Different radars in a composite can have the same task name but different sweeps.  
The composite method uses the sweep ID so it assumes that all the tasks have the same elevations.
- 6216: If the IRIS Analysis machine that works as socket server is set in local time, the IRIS Analysis products are shown in the wrong time in IRIS Focus. Vaisala recommends the user to setup the whole network in UTC time.
- 6382: Data manager is not able to read the IRIS RAW products generated from `odim_HDF5` files that do not contain all the required parameters.
- 6666: The events and alerts feature provides information in metric units throughout the configuration and display process.
- 6680: When the restart service of the web application is used, the application sometimes does not have time to change the settings properly. You must add a delay by running the following commands:

```
systemctl stop vaisala-radarsw-webapp
```

Wait approximately 15 seconds and then run:

```
systemctl start vaisala-radarsw-webapp
```

- The installation command for IRIS Focus 5.0 is now:
  - a. Change to the `/Focus_install` directory.
  - b. Run the IRIS Focus installation script:

```
/Focus_install/Vaisala-IRIS-Focus-v5.0.0--68/rsw-installer --offline --  
gis-db-dump vaisala-iris-maps-v2 --terrain-dir vaisala-iris-terrain-v2 -  
s <hostname or IP of IRIS Analysis socket server>
```

- The instructions in *IRIS Focus Administrator Guide* on making a manual back-up and restoring from a back-up are incomplete. See:
  - [Making a manual back-up \(page 40\)](#)
  - [Restoring from backup \(page 40\)](#)

## 8.4 Notes on Using IRIS Focus

### Viewing Radar Data

- The minimum screen resolution for viewing IRIS Focus is 1400 x 1050.
- In some cases, there may be missing or broken live radar products.
- In some cases, the lightning layer may be empty or missing.
- The image export service screen resolution maximum value is 3000 pixels in both axes.

### Browsers

- If you use **Remember Password** in your browser and login in first as a user and then as an admin, you may get an error message when you edit the user settings for other users.  
Despite the error message, your updates are saved in the system.
- Hardware acceleration may cause Firefox to crash with multiple products selected.  
To avoid the problem, in the Firefox menu select **Options > Advanced > Browsing** and uncheck **Use hardware acceleration when available**.

## 9. Backing up the data

### 9.1 Making a manual back-up

- ▶ 1. Log in as **root**.
- 2. Run: **/usr/vaisala/radarsw/backup/bin/do-backups**
- 3. Check that new files are created in the following directories:

```
/srv/vaisala/radarsw/backup/configuration/radarsw-configuration-  
<timestamp>.tar.gz
```

```
/srv/vaisala/radarsw/backup/database/database-wx-<timestamp>.gz
```

```
/srv/vaisala/radarsw/backup/database/database-vsp-<timestamp>.gz
```

Each backup file includes a timestamp in the format:

```
radarsw-configuration-2019-09-05T06-48-26.tar.gz
```

### 9.2 Restoring from backup

- ▶ 1. Log in as **root**.
- 2. Stop the Monit service:

```
systemctl stop monit.service
```

- 3. Stop the IRIS Focus web application:

```
systemctl stop vaisala-radarsw-webapp.service
```

4. (Optional) Run the backup script:  
`/usr/vaisala/radarsw/backup/bin/do-backups`
  - a. Copy the current configuration files to a remote host.
  - b. Copy the resulting configuration file to your own machine: `/srv/vaisala/radarsw/backup/configuration/radarsw-configuration-2019-10-12T09-42-18.tar.gz`
5. Copy the current database passwords from `/etc/vaisala/radarsw/configuration/vsoweb-override.ini`.  
 Save them in a text file.

```
[DATASOURCE]
datasource.password = xsGzN3ZK6kMqvaH6dzJQqAg1KwTMLnJL

[VSP_DATASOURCE]
datasource.password = AgbBwtr0XqDh64DgklkK6XqLXsnQP08U
```

6. Copy the current Data Manager password from `/etc/vaisala/radarsw/data-manager/data-manager-override.properties`.

```
/etc/vaisala/radarsw/data-manager/data-manager-override.properties
spring.datasource.password = bFKNUQ5fvFMfmsU3vWP3CEYJHVTu0J2Z
```

Save it in a text file.

7. Drop the current database with the `rsw-db-tool` utility:

```
rsw-db-tool drop-db
```

8. Recreate an empty database:

```
rsw-db-tool create-db
```

9. Switch to the database user account `postgres`:

```
su - postgres
```

10. Copy your backup files back to the Focus server and restore the database contents by reading the file contents into the standard output stream and inserting them in the IRIS Focus databases:

```
gzip --decompress --to-stdout /radarsw-database-vsp-2019-10-12T07-54-50.gz  
| psql vsp_v1  
gzip --decompress --to-stdout /radarsw-database-wx-2019-10-12T07-54-50.gz  
| psql wxdb2
```

11. Exit the postgres user shell:

```
exit
```

12. Start the IRIS Focus web application:

```
systemctl start vaisala-radarsw-webapp.service
```

13. Start the Monit service:

```
systemctl start monit.service
```

# Technical support



Contact Vaisala technical support at [helpdesk@vaisala.com](mailto:helpdesk@vaisala.com). Provide at least the following supporting information as applicable:

- Product name, model, and serial number
- Software/Firmware version
- Name and location of the installation site
- Name and contact information of a technical person who can provide further information on the problem

For more information, see [www.vaisala.com/support](http://www.vaisala.com/support).

# Warranty

For standard warranty terms and conditions, see [www.vaisala.com/warranty](http://www.vaisala.com/warranty).

Please observe that any such warranty may not be valid in case of damage due to normal wear and tear, exceptional operating conditions, negligent handling or installation, or unauthorized modifications. Please see the applicable supply contract or Conditions of Sale for details of the warranty for each product.

# Recycling



Recycle all applicable material.



Follow the statutory regulations for disposing of the product and packaging.





**VAISALA**

[www.vaisala.com](http://www.vaisala.com)

